

COMPLETE EDITION
ENGLISH VERSION

2019.12

special purpose
**telecommunication
products**
catalogue




Catalogo Prodotti di Telecomunicazione per Impieghi Speciali
Special Purpose Telecommunication Products Catalogue
2019.12.r17 Complete Edition - English Version

La riproduzione di tutto o parte di questo catalogo è autorizzata,
purché la provenienza risulti evidente e sia sempre citata.
*The reproduction of all or parts of this catalogue is authorized,
provided that the origin would be always evident and mentioned.*

La disponibilità, le caratteristiche ed i dati dei prodotti
sono soggetti a modifiche senza preavviso.
*Availability, specifications and products data
are subject to change without notice.*

© 2019 FITRE S.p.A. • Tutti i diritti riservati • *All rights reserved*



F fitre

1943·2018 ANNIVERSARY

75

FITRE is an industrial Company that has an enviable experience in the production of special communication equipment, as result of a more than seventy-five years presence in this sector, developing its products entirely in its own R&D laboratories, supporting the most innovative technologies and meeting the most stringent standards.

Therefore, since its foundation, **FITRE** bases its success on technical innovation and customer support.

Main activities concern products and equipment for Net Carriers, products and systems for Industrial Telecommunications and Public Emergency, products for SOHO and Business Telecommunications.

FITRE is also active in developing products and systems for communications and safety in hard environments, such as industrial plants, transports and public areas on territory.

To explore the different solutions, the wide range of products and to verify their conformity to your requirements, we invite you to visit our website www.fitresistemi.com

don't worry if you
mightn't find in here
the right product
you're looking for ...

... if that happens,
please, ask us for a
customized solution,
exploiting our skills
and our Italian wit,
to suit your needs.

special purpose telecommunication products catalogue



read this qr-code and
browse or download
the online catalogue
and its updates

Index

VoIP Phones Indoor	8
Access Panels for ASTRO PAGA SYSTEM EN 54-16:2008	11
VoIP Phones with handset	12
VoIP Phones handsfree	15
VoIP Phones handsfree alluminium 90x serie	19
VoIP Phones handsfree alluminium 95x serie	23
VoIP Phones handsfree steel	25
VoIP Phones ATEX	28
VoIP Phones decontaminable	31
Analog Phones with handset	33
Analog Phones handsfree	37
Analog Phones handsfree alluminium 90x serie	40
Analog Phones handsfree alluminium 95x serie	43
Analog Phones handsfree steel	45
Analog Phones ATEX	46
Analog Phones decontaminable	47
Analog Phones without keyboard	50
HOT-LINE Phones without keyboard	52
EMERGENCY CALL POINTS on board (EN 50155)	53

Index

EMERGENCY CALL POINTS for elevators	55
Monitoring System	57
Analog Local Battery Phones	58
Self-Powered Phones	59
Portable Phones	63
Accessories for Self Powered & Portable Phones	64
Signalling	66
Telephone Call Repeater Relays	68
Loudspeakers for Special Application	69
Loudspeakers Amplified	70
Loudspeakers accessories	73
Surge Protections	74
Telephone and Network Line Extenders	75
Pillars	76
Booth	78
Inductors & magnetic Switches	81
ASTRO SYSTEM components	84

INDOOR

P/N 7564410H TONO VOIP 8M-250MT



Operator Console suitable for Control Room and Supervisor suitable for handling:

- Emergency calls
- Telephone, Intercom and Emergency & Information functions
- Public Address and Alarm functions (P.A. and PAGA)
- Diagnostic functions, including the audio tests on handset, on hands-free as well on the auxiliary audio output
- 8 memory keys with LED

dimensions mm (W x H x D) 190,0 x 133,0 x 234,0

weight 1,75 kg

**HANDSET/HANDS-FREE
DESK MOUNTING**

IP30

0°C to + 50°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7564449H TONO VOIP 48M-250MT



Operator Console suitable for Control Room and Supervisor suitable for handling:

- Emergency calls
- Telephone, Intercom and Emergency & Information functions
- Public Address and Alarm functions (P.A. e PAGA)
- Diagnostic functions, including the audio tests on handset, on hands-free as well on the auxiliary audio output
- 48 memory keys with LED

dimensions mm (W x H x D) 285,0 x 133,0 x 234,0

**HANDSET/HANDS-FREE
DESK MOUNTING**

IP30

0°C to + 50°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7564482H TONO VOIP 88MEM-250MT



Operator Console suitable for Control Room and Supervisor equipped for handling:

- Emergency calls
- Telephone, Intercom, Emergency & Information functions
- Public Address and Alarm functions (P.A. & PAGA)
- Diagnostic functions, including the audio tests of handset, of hands-free as well as of the auxiliary audio outputs
- 88 memory keys with LED
- SIP protocol • PoE compatible
- Suitable for remote configuration and remote diagnostic

**HANDSET/HANDS-FREE
DESK MOUNTING**

IP30

0°C to + 50°C

**VOIP-VOIP-LINE
LENGTH:**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7564447 Gooseneck Microphone

Accessory for TONOVOIP telephone sets



Compact die-cast metal base with gooseneck, 480 mm length, for TONOVOIP telephone sets for P.A. announcement

dimensions mm footprint Ø120,0 x 480,0

weight 1,7 kg

INDOOR

P/N 7128180 TF615IP



- Digital telephone PoE compatible
- two SIP account • one IAX2 account
 - handsfree
 - multifunction graphics display
 - 4 function keys with LED • 3 fixed function keys
 - RJ9 jack for headset
 - switch 2 doors
 - desk/wall mounting

**HANDSET/HANDS-FREE
DESK/WALL MOUNTING**

dimensions mm (W x H) footprint 190,0 x 170,0

weight 990 g

P/N 7128181 DSS615



External console with 26 programmable function keys each with two-color LED

Accessory for TF615IP

DESK MOUNTING

dimensions mm (W x H x D) 90,0 x 170,0 x 120,0

weight 275 g

P/N 7128752 DECT300-HANDSET



- HD audio support (G.722)
- 2" TFT display (176x220)
- Polyphonic ring tones
- Local phonebook (100 entries)
- Remote (LDAP) and Central (3000 entries) phonebooks
- Headset connector (3.5mm) G722 codec for HD audio
- G726 codec for standard audio

**IP20
-10°C to +50°C**

P/N 7128777 DECT113-BASE RADIO



- Up to 3 repeaters per base station
- Wide band audio
- Automatic registration
- Max. 3 repeaters in daisy chain
- Indoor cabinet
- Manual mounting kit
- Easily mounted on walls
- 12 slot support
- Handling of 5 active narrow-band calls simultaneously
- Handling of 2 active wide-band calls simultaneously
- DECT encryption

**WALL MOUNTING
IP20
-10°C to +50°C**

dimensions 120,0 x 135,0 x 35,0 mm

INDOOR

P/N 7549070

SEL3010IP - RADIO REPEATER



- Frequency band: 1880 MHz – 1930 MHz (DECT)
1880 – 1900 MHz (10 carriers)
Europe - 1910 – 1930 MHz (10 carriers)
Latam - 1920 – 1930 MHz (5 carriers)
USand customized frequency bands
- Four power levels (14, 17, 20 and 24 dBm)
- Seamless handover using connection handover

WALL MOUNTING

IP20

- 5°C to + 55° C

dimensions 150,0 x 210,5 x 58,0 mm

INDOOR

P/N 7575121 DAP 54-16 /20



Console DAP EN 54-16 /20

The DAP EN 54-16 /20 operator station is part of the Fitre certified EN54-16 PA system. It allows you to manage various functions, including sending pre-recorded emergency announcements, sending live announcements via the gooseneck microphone, resetting system alarms, silencing emergency sound signals and other defined functions from the requirements of the EN54-16 standard.

dimensions mm (W x H x D) 191,0 x 133,0 x 234,0

**HANDS-FREE
DESK MOUNTING**

P/N 7575122 DAP 54-16 /60



Console DAP EN 54-16 /60

The DAP EN 54-16 /60 operator station is part of the Fitre certified EN54-16 PA system. It allows you to manage various functions, including sending pre-recorded emergency announcements, sending live announcements via the gooseneck microphone, resetting system alarms, silencing emergency sound signals and other defined functions from the requirements of the EN54-16 standard.

dimensions mm (W x H x D) 192,0 x 133,0 x 234,0

**HANDS-FREE
DESK MOUNTING**

P/N 7575123 DAP 54-16 /100



Console DAP EN 54-16 /100

The DAP EN 54-16 /100 operator station is part of the Fitre certified EN54-16 PA system. It allows you to manage various functions, including sending pre-recorded emergency announcements, sending live announcements via the gooseneck microphone, resetting system alarms, silencing emergency sound signals and other defined functions from the requirements of the EN54-16 standard.

dimensions mm (W x H x D) 287,0 x 133,0 x 234,0

**HANDS-FREE
DESK MOUNTING**

P/N 7575124 DAP 54-16 /140



Console DAP EN 54-16 /140

The DAP EN 54-16 /140 operator station is part of the Fitre certified EN54-16 PA system. It allows you to manage various functions, including sending pre-recorded emergency announcements, sending live announcements via the gooseneck microphone, resetting system alarms, silencing emergency sound signals and other defined functions from the requirements of the EN54-16 standard.

dimensions mm (W x H x D) 382,0 x 133,0 x 234,0

**HANDS-FREE
DESK MOUNTING**

VoIP Phones with handset

WEATHERPROOF

P/N 7564470H TAS2000 VOIP PHONE/INTERCOM-250MT



VoIP weatherproof and vandalproof telephone with handset

- IP66 protection
- die cast "copper-free" aluminium alloy case
- adjustable receiver volume
- With full 12 keys keyboard
- 4 function keys and 4 programmable memory keys
- SIP protocol • PoE compatible
- Suitable for remote configuration and remote diagnostic

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7564470HR TAS2000 VOIP PHONE/INTERCOM-250MT+I/O



VoIP weatherproof and vandalproof telephone with handset

- IP66 protection
- die cast "copper-free" aluminium alloy case
- adjustable receiver volume
- With full 12 keys keyboard
- 4 function keys and 4 programmable memory keys
- SIP protocol • PoE compatible
- Suitable for remote configuration and remote diagnostic
- With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7564473 TAS2000 VOIP A-TEL



VoIP weatherproof and vandalproof telephone with handset

- IP66 protection
- die cast "copper free" aluminium alloy case
- Backlighted display with 2 rows x 16 characters
- Full keyboard whit display navigation keys and 4 speed dialling keys, 4 direct memory keys
- Volume adjustable
- SIP protocol, PoE compatible
- Suitable for remote configuration and diagnostic
- Interface with output relay for external loudspeaker
- Operating temperature - 40°C to + 70°C

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7564432H TAS2000 VOIP 1M-250MT



VoIP weatherproof and vandalproof telephone with handset

- IP66 protection • die cast "copper-free" aluminium alloy case
- 1 programmable memory key
- SIP protocol • PoE compatible
- Suitable for remote configuration and diagnostic

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

VoIP Phones with handset

WEATHERPROOF

P/N 756444HR TAS2000 VOIP 4M-250MT+I/O



- VoIP weatherproof and vandalproof telephone with handset
- IP66 protection
 - die cast "copper-free" aluminium alloy case
 - Both "powerful-duplex" (DSP based) handsfree and handset
 - adjustable receiver volume
 - 4 programmable memory keys
 - SIP protocol • PoE compatible
 - Suitable for remote configuration and diagnostic
 - With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET/HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7564400H TAS2000 VOIP 26K 2L-250MT



- VoIP weatherproof and vandalproof telephone with handset
- IP66 protection
 - die cast "copper-free" aluminium alloy case
 - Both "powerful-duplex" (DSP based) handsfree and handset
 - adjustable receiver volume
 - With full 12 keys keyboard
 - 4 function keys and 4 programmable memory keys
 - SIP protocol • PoE compatible
 - Suitable for remote configuration and diagnostic

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET/HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7564400HR TAS2000 VOIP 26K 2L-250MT+I/O



- VoIP weatherproof and vandalproof telephone with handset
- IP66 protection
 - die cast "copper-free" aluminium alloy case
 - Both "powerful-duplex" (DSP based) handsfree and handset
 - adjustable receiver volume
 - With full 12 keys keyboard
 - 4 function keys and 4 programmable memory keys
 - SIP protocol • PoE compatible
 - Suitable for remote configuration and diagnostic
 - With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET/HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7564400HX TAS2000 VOIP 26K 2L-250MT+AUX



- VoIP weatherproof and vandalproof telephone with handset
- IP66 protection
 - die cast "copper-free" aluminium alloy case
 - Both "powerful-duplex" (DSP based) handsfree and handset
 - adjustable receiver volume
 - With full 12 keys keyboard
 - 4 function keys and 4 programmable memory keys
 - SIP protocol • PoE compatible
 - Suitable for remote configuration and diagnostic
 - analog audio output card for optional external amplified loudspeakers

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET/HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

WEATHERPROOF

P/N D001153 TAS2000 BLS - FOR BLUE LIGHT STATIONS



VoIP Blue Light Station, weatherproof & vandalproof telephone with handset

- IP66 protection
- die cast "copper-free" aluminium alloy case
- 2 programmable memory keys
- SIP protocol • PoE compatible
- Suitable for remote configuration and remote diagnostic

dimensions mm (W x H x D) 232,0 x 324,0 x 142,5

HANDSET

WALL MOUNTING

IP66

- 20°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 75644xxHR TAS2000 VOIP I/O 250MT



VoIP weatherproof and vandalproof telephone with handset

- IP66 protection • die cast "copper-free" aluminium alloy case
- Automatic call to a pre-recorded number when the handset is released
- SIP protocol • PoE compatible
- Suitable for remote configuration and diagnostic

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N D001170 TAS2000 VOIP HOT-LINE SYSTEM



- HOT-LINE System without IP-PBX
- Up to eight Industrial TAS2000 VOIP phone with handset
- When one phone is unhooked then all the other phones of the system will ring
- External ringers and beacons can be added as option
- Any unhooked phone of the system stops its ringing and is added to the "CONFERENCE" conversation (Party-Line)

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

WEATHERPROOF

P/N 7133160H TAS360 VOIP 20K-6L-250MT



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 20 keys (full 12 keys keyboard + 4 function keys + 4 programmable memory keys + 6 lights)
- SIP protocol • PoE compatible

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133160HR TAS360 VOIP 20K-6L-250MT+I/O



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 20 keys (full 12 keys keyboard + 4 function keys + 4 programmable memory keys + 6 lights)
- SIP protocol • PoE compatible
- With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133160HX TAS360 VOIP 20K-6L-250MT+AUX



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 20 keys (full 12 keys keyboard + 4 function keys + 4 programmable memory keys + 6 lights)
- SIP protocol • PoE compatible
- analog audio output card for optional external amplified loudspeakers

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133143 TAS360 VOIP 1M V1.3



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 1 memory key
- SIP protocol • PoE compatible

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

WEATHERPROOF

P/N 7133143H TAS360 VOIP 1M-250MT



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 1 memory key
- SIP protocol • PoE compatible

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133143HR TAS360 VOIP 1M-250 MT+I/O



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 1 memory key
- SIP protocol • PoE compatible
- With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133143HX TAS360 VOIP 1M-250 MT+AUX



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 1 memory key
- SIP protocol • PoE compatible
- analog audio output card for optional external amplified loudspeakers

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133165 TAS360 VOIP 8K-6L



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 4 programmable memory keys and 4 function keys + 6 lights
- SIP protocol
- PoE compatible

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

WEATHERPROOF

P/N 7133165H TAS360 VOIP 8K-6L-250MT



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 4 programmable memory keys and 4 function keys + 6 lights
- SIP protocol
- PoE compatible

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133165HR TAS360 VOIP 8K-6L-250MT+I/O



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 4 programmable memory keys and 4 function keys + 6 lights
- SIP protocol
- PoE compatible
- With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133165HX TAS360 VOIP 8K-6L-250MT+AUX



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 4 programmable memory keys and 4 function keys + 6 lights
- SIP protocol
- PoE compatible
- analog audio output card for optional external amplified loudspeakers

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,3 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N D001169 TAS360 VOIP-BLS



VoIP weatherproof and vandalproof "powerful - duplex" handsfree (DSP based) telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- 1 LED showing the STATION IS AVAILABLE FOR CALLING
- 1 LED showing the station status CALL IN PROGRESS
- 1 push-button EMERGENCY CALL
- 1 Blue light flashing lamp
- SIP protocol • PoE compatible

dimensions mm (W x H x D) 142,5 x 560,0 x 135,0

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

WEATHERPROOF

P/N 7132701H TASVOIP GRP 1M/SOS-250MT



Digital VoIP telephone (standard SIP) for wall mount installation

- Weatherproof IP65 GRP housing
- Hands-free conversation
- Large mushroom head direct SOS call key
- Operating Temperature: -40°C to +70°C
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)

OPTION: analog audio output for handling the optional external amplified loudspeaker

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 2,4 kg

HANDS-FREE

WALL MOUNTING

IP65

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

VoIP Phones handsfree alluminium 90x serie

WEATHERPROOF

P/N 7133340 TASVOIP 916



- Digital telephone flush mounting
- weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol - complete keyboard + 2 memory keys

HANDS-FREE
FLUSH MOUNTING
IP65
- 20°C to + 70°C

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

P/N 7133340H TASVOIP 916-250MT



- Digital telephone flush mounting
- weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol - complete keyboard + 2 memory keys

HANDS-FREE
FLUSH MOUNTING
IP65
- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

P/N 7133301H TASVOIP 901-250MT



- Digital telephone
- flush mounting
 - weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol
 - 1 programmable call key

HANDS-FREE
FLUSH MOUNTING
IP65
- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

P/N 7133301AH TASVOIP 901-250MT



- Digital telephone
- flush mounting
 - weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol
 - 1 programmable call key

HANDS-FREE
FLUSH MOUNTING
IP65
- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

VoIP Phones handsfree alluminium 90x serie

WEATHERPROOF

P/N 7133311 TASVOIP 901/SOS



- Digital telephone flush mounting
- weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol - 1 SOS programmable call key

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

HANDS-FREE
FLUSH MOUNTING
IP65
- 20°C to + 70°C

P/N 7133312H TASVOIP 902/INFO-SOS-250MT



- Digital telephone flush mounting
- weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol - 2 INFO-SOS programmable call keys

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

HANDS-FREE
FLUSH MOUNTING
IP65
- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

P/N 7133304 TASVOIP 904



- Digital telephone flush mounting
- weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol - 4 programmable call keys

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

HANDS-FREE
FLUSH MOUNTING
IP65
- 20°C to + 70°C

Option:
Remote Monitoring by
ASTRO System Manager

P/N 7133304H TASVOIP 904-250MT



- Digital telephone flush mounting
- weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol - 4 programmable call keys

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

HANDS-FREE
FLUSH MOUNTING
IP65
- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

VoIP Phones handsfree alluminium 90x serie

WEATHERPROOF

P/N 7133308 TASVOIP 908



- Digital telephone flush mounting
- weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol - 8 programmable call keys

HANDS-FREE
FLUSH MOUNTING
IP65
- 20°C to + 70°C

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

P/N 7133308H TASVOIP 908-250MT



- Digital telephone flush mounting
- weatherproof 4mm thick aluminium alloy plate IP65 protection
 - hands-free real full-duplex conversation with echo cancellation
 - RJ45 Ethernet interface with PoE and/or local power supply (22 to 57VDC)
 - SIP protocol - 8 programmable call keys

HANDS-FREE
FLUSH MOUNTING
IP65
- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 930 g

P/N 7133800 DESK CASE



- Desk case
- natural anodized aluminium; black base
 - equipped with screws for mounting telephones of the 900 series

Accessory for 900 telephone series

dimensions mm (W x H x D) 105,0 x 265,0 x 160,0

weight 350 g

P/N 7133005 PROTRUDING ROOF

Accessory for 900 telephone series



- Protruding aluminium roof
- to be added to the flush mounting telephone plate

dimensions mm (W x H x D) 105,0 x 258,0 x 30,0

WEATHERPROOF

P/N 7133006 PROTRUDING CASE

Accessory for 900 telephone series



Anodized aluminium case for protruding wall mounting
• built-in roof for a higher protection from bad weather

dimensions mm (W x H x D) 105,0 x 258,0 x 100,0

P/N 7133004 PROTRUDING CASE

Accessory for 900 telephone series



Natural anodized aluminium case for protruding wall mounting

dimensions mm (W x H x D) 105,0 x 258,0 x 70,0

VoIP Phones handsfree alluminium 95x serie

WEATHERPROOF

P/N 7133361H TASVOIP 951/SOS-250MT



Digital VoIP telephone (standard SIP) for flush mount installation

- built on weatherproof IP66 aluminium plate and IP66 rear protection
- Hands-free conversation
- Vandal-proof
- equipped with 1 direct SOS call key
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)

dimensions mm (W x H x D) 195,0 x 330,0 x 81,0

weight 1,97 kg

HANDS-FREE
FLUSH MOUNTING
IP66

- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

P/N 7133361HR TASVOIP 951/SOS-250MT+I/O



Digital VoIP telephone (standard SIP) for flush mount installation

- built on weatherproof IP66 aluminium plate and IP66 rear protection
- Hands-free conversation
- Vandal-proof
- equipped with 1 direct SOS call key
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)
- With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

dimensions mm (W x H x D) 195,0 x 330,0 x 81,0

weight 1,97 kg

HANDS-FREE
FLUSH MOUNTING
IP66

- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

P/N 7133372 TASVOIP 952/INFO-SOS IL



Digital VoIP telephone (standard SIP) for flush mount installation

- built on weatherproof IP66 aluminium plate and IP66 rear protection
- Hands-free conversation
- Vandal-proof
- equipped with 1 direct SOS call key and 1 direct INFO call key
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)
- It is configured with the additional "Inductor Loop" device in order to support the communication with Hearing-Impaired person

dimensions mm (W x H x D) 195,0 x 330,0 x 81,0

weight 1,97 kg

HANDS-FREE
FLUSH MOUNTING
IP66

- 40°C to + 70°C

Option:
Remote Monitoring by
ASTRO System Manager

P/N 7133372H TASVOIP 952/INFO-SOS IL-250MT



Digital VoIP telephone (standard SIP) for flush mount installation

- built on weatherproof IP66 aluminium plate and IP66 rear protection
- Hands-free conversation
- Vandal-proof
- equipped with 1 direct SOS call key and 1 direct INFO call key
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)
- It is configured with the additional "Inductor Loop" device in order to support the communication with Hearing-Impaired person

dimensions mm (W x H x D) 195,0 x 330,0 x 81,0

weight 1,97 kg

HANDS-FREE
FLUSH MOUNTING
IP66

- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

WEATHERPROOF

P/N 7133362H TASVOIP 952/INFO-SOS-250MT



Digital VoIP telephone (standard SIP) for flush mount installation

- built on weatherproof IP66 aluminium plate and IP66 rear protection
- Hands-free conversation
- Vandal-proof
- equipped with 1 direct SOS call key and 1 direct INFO call key
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)

dimensions mm (W x H x D) 195,0 x 330,0 x 81,0

weight 1,97 kg

HANDS-FREE
FLUSH MOUNTING
IP66

- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

P/N 7133362HR TASVOIP 952/INFO-SOS-250MT+I/O



Digital VoIP telephone (standard SIP) for flush mount installation

- built on weatherproof IP66 aluminium plate and IP66 rear protection
- Hands-free conversation
- Vandal-proof
- equipped with 1 direct SOS call key and 1 direct INFO call key
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)
- With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

dimensions mm (W x H x D) 195,0 x 330,0 x 81,0

weight 1,97 kg

HANDS-FREE
FLUSH MOUNTING
IP66

- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

P/N 71331xi E-TEL FLUSH MOUNT EMERGENCY CALL POINT



- EMERGENCY CALL POINT VoIP TELEPHONE (SIP standard) with Direct Call Button and Call Status visual indication
- Vandal-proof, brushed stainless steel made
- NEMA 4X protection grade enclosure
- IK07 protection DEGREE against external mechanical impacts (EN-62262)
- Full-duplex hands-free conversation
- Auto-Answering and Silent Monitoring features for environmental monitoring and control
- Output: 2 relays max.1A or 250VAC, max power 60VA/30WDC
- Input: n.3 voltage free

IP65

- 25°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 71331xl E-TEL/BOX WALL MOUNT EMERGENCY CALL POINT



- EMERGENCY CALL POINT VoIP TELEPHONE (SIP standard) with Direct Call Button and Call Status visual indication
- Vandal-proof, brushed stainless steel made
- NEMA 4X protection grade enclosure
- IK07 protection degree against external mechanical impacts (EN-62262)
- Full-duplex hands-free conversation
- Auto-Answering and Silent Monitoring features for environmental monitoring and control
- Output: 2 relays max.1A or 250VAC, max power 60VA/30WDC
- Input: n.3 voltage free

IP65

- 25°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 71331xm P-TEL FLUSH MOUNT ASSISTANCE PHONE



- PASSENGER INFORMATION VoIP TELEPHONE (SIP standard) with Direct Call Button and Call Status visual indication
- Vandal-proof, brushed stainless steel made
- NEMA 4X protection grade enclosure
- IK07 protection degree against external mechanical impacts (EN-62262)
- Full-duplex hands-free conversation
- Auto-Answering and Silent Monitoring features for environmental monitoring and control
- Output: 2 relays max.1A or 250VAC, max power 60VA/30WDC
- Input: n.3 voltage free

IP65

- 25°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 71331xn P-TEL/BOX WALL MOUNT ASSISTANCE PHONE



- PASSENGER INFORMATION VoIP TELEPHONE (SIP standard) with Direct Call Button and Call Status visual indication
- Vandal-proof, brushed stainless steel made
- NEMA 4X protection grade enclosure
- IK07 protection degree against external mechanical impacts (EN-62262)
- Full-duplex hands-free conversation
- Auto-Answering and Silent Monitoring features for environmental monitoring and control
- Output: 2 relays max.1A or 250VAC, max power 60VA/30WDC
- Input: n.3 voltage free

IP65

- 25°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

WEATHERPROOF

P/N 7133320H TASVOIP 1004/ST-250MT



VoIP industrial weatherproof and vandalproof telephone set for flush mounting installation

- built on steel AISI304, IP66 plate
- based on standard SIP protocol
- Hands-free real full-duplex operation
- no keys, but able to be connected to 4 programmable external keys
- special version for SOS boxes for road tunnels

**HANDS-FREE
FLUSH MOUNTING
IP66**

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 180,0 x 260,0 x 57,0

weight 1,45 kg

P/N 7133320HR TASVOIP 1004/ST I/O-250MT



VoIP industrial weatherproof and vandalproof telephone set for flush mounting installation

- built on steel AISI304, IP66 plate
- based on standard SIP protocol
- Hands-free real full-duplex operation
- no keys, but able to be connected to 4 programmable external keys
- special version for SOS boxes for road tunnels
- With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

**HANDS-FREE
FLUSH MOUNTING
IP66**

- 40°C to + 70°C


**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 180,0 x 260,0 x 82,0

weight 1,45 kg

P/N 7133028 Plate




Aluminium face plate 3mm thickness

- painted yellow RAL1023
- equipped with 4 mushroom push buttons and screen printed symbols "Ambulance", "Fire", "Police", "Breakdown"
- for installation of a telephone type TASVOX or TASVOIP 1004 series in a SOS tunnel cabinet

dimensions mm (W x H x D) 496,0 x 748, x 35,0

P/N 7133323H TASVOIP 961/SOS FOR EMERGENCY CALL POINTS



- Digital VoIP telephone (standard SIP) for flush mount installation built on stainless steel AISI304 weatherproof IP66 plate
- Protection against external mechanical impacts IK07 (EN62262)
- Hands-free conversation
- Vandal-proof equipped with two direct call keys
- 1 direct call key (SOS-EMERGENCY)
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)
- SIP protocol • PoE compatible
- Suitable for remote configuration and remote diagnostic

**HANDS-FREE
FLUSH MOUNTING
IP66**

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 155,0 x 275,0 x 75,0

weight 1,35 kg

WEATHERPROOF

P/N 7133325H TASVOIP 962/INFO-SOS FOR EMERGENCY CALL POINTS



- Digital VoIP telephone (standard SIP) for flush mount installation built on stainless steel AISI304 weatherproof IP66 plate
- Protection against external mechanical impacts IK07 (EN62262)
- Hands-free conversation
- Vandal-proof equipped with two direct call keys
- 2 direct call keys (INFORMATION/EMERGENCY)
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)
- SIP protocol • PoE compatible
- Suitable for remote configuration and remote diagnostic

dimensions mm (W x H x D) 155,0 x 275,0 x 75,0

weight 1,35 kg

**HANDS-FREE
FLUSH MOUNTING
IP66**

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133325HR TASVOIP 962/INFO-SOS-250MT+I/O



- Digital VoIP telephone (standard SIP) for flush mount installation built on stainless steel AISI304 weatherproof IP66 plate
- Protection against external mechanical impacts IK07 (EN62262)
- Hands-free conversation
- Vandal-proof equipped with two direct call keys
- 2 direct call keys (INFORMATION/EMERGENCY)
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)
- SIP protocol • PoE compatible
- Suitable for remote configuration and remote diagnostic
- With I/O card (n.4 ON/OFF or voltage command inputs and n.2 output relays)

dimensions mm (W x H x D) 155,0 x 275,0 x 75,0

weight 1,35 kg

**HANDS-FREE
FLUSH MOUNTING
IP66**

- 40°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 71333xh TASVOIP 952H-250MT INFO/SOS CALL POINTS



- Digital VoIP telephone (standard SIP) for flush mount installation built on weatherproof IP65 vandal-proof stainless steel plate
- Hands-free conversation
- Large head direct call keys
- Available with 1 or 2 direct call keys
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)
- Integrated mechanical support for fixing the CCTV camera (not included) equipped with vandal-proof glass
- SIP protocol • PoE compatible

dimensions mm (W x H x D) 200,0 x 430,0 x 74,3

weight 1,750 kg

**HANDS-FREE
FLUSH MOUNTING
IP65**

- 25°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133343H TASVOIP 952H-250MT INFO/SOS CALL POINTS



- Digital VoIP telephone (standard SIP) for flush mount installation built on weatherproof IP65 vandal-proof stainless steel plate painted red RAL3000
- Hands-free conversation
- Large head direct call keys
- Available with 1 or 2 direct call keys
- RJ45 Ethernet interface with PoE and/or local power supply (22 to 56 VDC)
- Integrated mechanical support for fixing the CCTV camera (not included) equipped with vandal-proof glass
- SIP protocol • PoE compatible

dimensions mm (W x H x D) 200,0 x 430,0 x 74,3

weight 1,750 kg

**HANDS-FREE
FLUSH MOUNTING
IP65**

- 25°C to + 70°C

**VOIP-LINE LENGTH:
UP TO 250 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

EXPLOSION-PROOF

P/N 7134401 TAS2000 VoIP-Ex 22K-2L-TEL



Explosion-proof VoIP Telephone/Intercom Station with handset

- SIP protocol • PoE compatible
- Protection class IP66 • ATEX certified for Zone 1 - Zone 21
- Standard keyboard
- 4 memory keys for direct calls • 4 service keys
- 2 lights
- volume adjusting +/- keys

ATEX Approval:

II 2G Ex e mb ib IIC T6 (@Tamb.<40°C), T5 (@Tamb.<55°C) Gb

II 2D Ex tb IIIC T85°C (@Tamb.<40°C), T100°C (@Tamb.<55°C) Db IP66

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 6,0 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 55°C

ATEX

**VOIP-LINE LENGTH:
UP TO 180 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7134402 TAS2000 VoIP-Ex 6K-2L-MX1



Explosion-proof VoIP Intercom Station with handset

- SIP protocol • PoE compatible
- Protection class IP66 • ATEX certified for Zone 1 - Zone 21
- 1 general call • 1 conversation line
- 3 alarm keys
- 2 lights
- volume adjusting +/- keys

ATEX Approval:

II 2G Ex e mb ib IIC T6 (@Tamb.<40°C), T5 (@Tamb.<55°C) Gb

II 2D Ex tb IIIC T85°C (@Tamb.<40°C), T100°C (@Tamb.<55°C) Db IP66

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 6,0 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 55°C

ATEX

**VOIP-LINE LENGTH:
UP TO 180 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7134403 TAS2000 VoIP-Ex 11K-6L-MX2



Explosion-proof VoIP Intercom Station with handset

- SIP protocol • PoE compatible
- Protection class IP66 • ATEX certified for Zone 1 - Zone 21
- 1 general call • 5 conversation lines
- 3 alarm keys
- 6 lights
- volume adjusting +/- keys

ATEX Approval:

II 2G Ex e mb ib IIC T6 (@Tamb.<40°C), T5 (@Tamb.<55°C) Gb

II 2D Ex tb IIIC T85°C (@Tamb.<40°C), T100°C (@Tamb.<55°C) Db IP66

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 6,0 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 55°C

ATEX

**VOIP-LINE LENGTH:
UP TO 180 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7134601N TAS360 VoIP-Ex 20K-6L-IS2



Explosion-proof VoIP hands-free Intercom Station

- SIP protocol • PoE compatible
- Protection class IP66 • ATEX certified for Zone 1 - Zone 21
- Standard keyboard
- 4 memory keys for direct calls • 4 service keys
- 6 lights

ATEX Approval:

II 2G Ex e mb ib IIC T6 (@Tamb.<40°C), T5 (@Tamb.<55°C) Gb

II 2D Ex tb IIIC T85°C (@Tamb.<40°C), T100°C (@Tamb.<55°C) Db IP66

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 4,1 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 55°C

ATEX

**VOIP-LINE LENGTH:
UP TO 180 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

EXPLOSION-PROOF

P/N 7134602N TAS360 VoIP-Ex 8K-6L-IS2



Explosion-proof VoIP hands-free Intercom Station

- SIP protocol • PoE compatible
- Protection class IP66 • ATEX certified for Zone 1 - Zone 21
- 4 memory keys • 4 function keys
- 6 lights

ATEX Approval:
 II 2G Ex e mb ib IIC T6 (@Tamb.<40°C), T5 (@Tamb.<55°C) Gb
 II 2D Ex tb IIIC T85°C (@Tamb.<40°C), T100°C (@Tamb.<55°C) Db IP66

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 4,1 kg

HANDS-FREE
WALL MOUNTING
IP66
 - 40°C to + 55°C
ATEX

VOIP-LINE LENGTH:
UP TO 180 Meters

Option:
 Remote Monitoring by
 ASTRO System Manager

P/N 7134603 TAS360 VoIP-Ex 7K-2L-MX1



Explosion-proof VoIP hands-free Intercom Station

- SIP protocol • PoE compatible
- Protection class IP66 • ATEX certified for Zone 1 - Zone 21
- 1 general call • 1 conversation line
- 3 alarm keys
- 2 lights
- volume adjusting +/- keys

ATEX Approval:
 II 2G Ex e mb ib IIC T6 (@Tamb.<40°C), T5 (@Tamb.<55°C) Gb
 II 2D Ex tb IIIC T85°C (@Tamb.<40°C), T100°C (@Tamb.<55°C) Db IP66

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 4,1 kg

HANDS-FREE
WALL MOUNTING
IP66
 - 40°C to + 55°C
ATEX

VOIP-LINE LENGTH:
UP TO 180 Meters

Option:
 Remote Monitoring by
 ASTRO System Manager

P/N 7134604 TAS360 VoIP-Ex 10K-7L-MX2



Explosion-proof VoIP hands-free Intercom Station

- SIP protocol • PoE compatible
- Protection class IP66 • ATEX certified for Zone 1 - Zone 21
- 1 general call • 6 conversation lines
- 7 lights
- volume adjusting +/- keys

ATEX Approval:
 II 2G Ex e mb ib IIC T6 (@Tamb.<40°C), T5 (@Tamb.<55°C) Gb
 II 2D Ex tb IIIC T85°C (@Tamb.<40°C), T100°C (@Tamb.<55°C) Db IP66

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 4,1 kg

HANDS-FREE
WALL MOUNTING
IP66
 - 40°C to + 55°C
ATEX

VOIP-LINE LENGTH:
UP TO 180 Meters

Option:
 Remote Monitoring by
 ASTRO System Manager

P/N 71346xx TAS360 VoIP-Ex-1M



Explosion-proof VoIP hands-free Intercom Station

- SIP protocol • PoE compatible
- Protection class IP66 • ATEX certified for Zone 1 - Zone 21
- 1 conversation line
- 2 lights

ATEX Approval:
 II 2G Ex e mb ib IIC T6 (@Tamb.<40°C), T5 (@Tamb.<55°C) Gb
 II 2D Ex tb IIIC T85°C (@Tamb.<40°C), T100°C (@Tamb.<55°C) Db IP66

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 4,1 kg

HANDS-FREE
WALL MOUNTING
IP66
 - 40°C to + 55°C
ATEX

VOIP-LINE LENGTH:
UP TO 180 Meters

Option:
 Remote Monitoring by
 ASTRO System Manager

EXPLOSION-PROOF

P/N 7134605 TAS360 VoIP-Ex 5K-2L-MX3



Explosion-proof VoIP hands-free Intercom Station

- SIP protocol • PoE compatible
- Protection class IP66 • ATEX certified for Zone 1 - Zone 21
- 1 conversation line
- 2 lights
- volume adjusting +/- keys

ATEX Approval:

II 2G Ex e mb ib IIC T6 (@Tamb.<40°C), T5 (@Tamb.<55°C) Gb

II 2D Ex tb IIIC T85°C (@Tamb.<40°C), T100°C (@Tamb.<55°C) Db IP66

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 4,1 kg

HANDS-FREE

WALL MOUNTING

IP66

- 40°C to + 55°C

ATEX

**VOIP-LINE LENGTH:
UP TO 180 Meters**

*Option:
Remote Monitoring by
ASTRO System Manager*

DECONTAMINABLE

P/N 7564440V SANIVOIP 918S V1.3



- VoIP telephone for clean-rooms - flush mounting
- front surface IP66 weatherproof without holes and fully washable by common detergents or bactericides
 - 12 standard dialling keys and 6 function keys
 - adjustable receiver volume
 - slim thickness 34mm depth only

HANDS-FREE
FLUSH MOUNTING
IP66
- 40°C to + 70°C

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 125,0 x 280,0 x 34,0

weight 900 g

P/N 7564440H SANIVOIP 918S-250MT



- VoIP telephone for clean-rooms - flush mounting
- front surface IP66 weatherproof without holes and fully washable by common detergents or bactericides
 - 12 standard dialling keys and 6 function keys
 - adjustable receiver volume
 - slim thickness 34mm depth only

HANDS-FREE
FLUSH MOUNTING
IP66
- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 125,0 x 280,0 x 34,0

weight 900 g

P/N 7564461H SANIVOIP 901S-250MT



- VoIP telephone for clean-rooms - flush mounting
- front surface IP66 weatherproof without holes and fully washable by common detergents or bactericides
 - 1 memory key
 - slim thickness 34mm depth only

HANDS-FREE
FLUSH MOUNTING
IP66
- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

Product manufactured upon request. MOQ 25 pcs

dimensions mm (W x H x D) 125,0 x 280,0 x 34,0

weight 900 g

P/N 7564464H SANIVOIP 904S-250MT



- VoIP telephone for clean-rooms - flush mounting
- front surface IP66 weatherproof without holes and fully washable by common detergents or bactericides
 - 4 memory keys
 - slim thickness 34mm depth only

HANDS-FREE
FLUSH MOUNTING
IP66
- 40°C to + 70°C

VOIP-LINE LENGTH:
UP TO 250 Meters

Option:
Remote Monitoring by
ASTRO System Manager

Product manufactured upon request. MOQ 25 pcs

dimensions mm (W x H x D) 125,0 x 280,0 x 34,0

weight 900 g

DECONTAMINABLE

P/N 7564468 SANIVOIP 908S



- VoIP telephone for clean-rooms - flush mounting
- front surface IP66 weatherproof without holes and fully washable by common detergents or bactericides
 - 8 memory keys
 - slim thickness 34mm depth only

Product usually available ex-stock

HANDS-FREE
FLUSH MOUNTING
IP66
- 20°C to + 70°C

*Option:
 Remote Monitoring by
 ASTRO System Manager*

dimensions mm (W x H x D) 125,0 x 280,0 x 34,0

weight 900 g

P/N 8131931 BACK-BOX

Accessory for decontaminable SANIVOIP telephone sets



Galvanized steel back-box for concrete wall installation of SANIVOX-SANIVOIP series telephone sets

- It is not necessary for installation on metal or plastic panels or sandwich panels

dimensions mm (W x H x D) 107,0 x 265,0 x 56,0

weight 400 g

P/N 7133060 BACK-BOX

Accessory for decontaminable SANIVOIP telephone sets



Stainless steel back-box for surface installation of SANIVOX-SANIVOIP series telephone sets as alternative to the flush mounting installation

dimensions mm (W x H x D) 135,0 x 290,0 x 36,5

weight 440 g

Analog Phones with handset

INDOOR

P/N 7128746A TF205



Wall/desk PSTN Analog indoor telephone light grey colour

- 2 memories

HANDSET
DESK MOUNTING

dimensions mm (W x H) footprint 158,0 x 219,0

weight 960 g

P/N 7128734 TF425 green



Line-powered multifunction analog telephone with CLIP function

- hands-free communication and headset jack
- with alphanumeric display
- 6 two-level memory keys for direct dialling
- Phonebook for 150 numbers with name

HANDSET
DESK MOUNTING

dimensions mm (W x H) footprint 210,0 x 198,0

weight 1,25 kg

WEATHERPROOF

P/N 7132445CFX TAS2000 RV



Analog ACB weatherproof and vandalproof telephone

- IP66 protection
- standard telephone keyboard
- die cast "copper free" aluminium alloy case, (suitable for petro-chemical environments)
- adjustable volume receiver (Vol + / Vol - keys)
- adjustable volume loud bell (95 dB at 1m)

HANDSET
WALL MOUNTING
IP66
- 40°C to + 70°C

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,5 kg

P/N 7132459X TAS2000 MEMO 8MTC/ST



Analog ACB weatherproof and vandalproof telephone

- IP66 protection
- die cast "copper-free" aluminium alloy case
- full keyboard with 8 memory keys for calls towards 8 programmable numbers
- With headset connector
- Adjustable receiver volume

HANDSET
WALL MOUNTING
IP66
- 40°C to + 70°C

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,8 kg

Analog Phones with handset

WEATHERPROOF

P/N 7132471X TAS2000 MEMO 10MT/ST



- Analog ACB weatherproof and vandalproof telephone
- IP66 protection
 - die cast "copper-free" aluminium alloy case
 - full keyboard with 10 memory keys for calls towards 10 programmable numbers
 - Adjustable receiver volume

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,80kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 70°C

P/N 7132458X TAS2000 MEMO 8MTC/NC



- Analog ACB weatherproof and vandalproof telephone
- IP66 protection
 - die cast "copper-free" aluminium alloy case
 - full keyboard with 8 memory keys for calls towards 8 programmable numbers
 - With headset connector
 - With special handset having a noise cancelling microphone for noisy environments (e.g: Engine-Room of the ships)
 - Adjustable receiver volume

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,8 kg

HANDSET

WALL MOUNTING

IP66

- 40°C to + 70°C

P/N 7148913 RI70/T

Accessory for TAS2000MEMO



- Industrial headset with dynamic microphone
- weatherproof plug for TAS2000MEMO 8M TC SA/NC telephone set (P/N 7132458X)

weight 360 g

P/N 7133690 TAS2000 VOX



- Analog ACB weatherproof and vandalproof telephone
- IP66 protection
 - die cast "copper-free" aluminium alloy case
 - both full-duplex handsfree and handset
 - 4 keys for calling programmable numbers - adjustable receiver volume
 - Suitable for remote configuration and diagnostics (Astro System Manager)
 - Full-duplex
 - handsfree

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 6,0 kg

HANDSET/HANDS-FREE

WALL MOUNTING

IP66

- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

Analog Phones with handset

WEATHERPROOF

P/N 7132801 TTS10 32P



Analog ACB telephone

- GRP polyester case
- 15 keys keyboard
- wall mounting
- IP65 protection

HANDSET

WALL MOUNTING

IP65

- 20°C to + 70°C

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 2,65 kg

P/N J7111420 TTSVOX-BCA-MT



Analog ACB telephone

- GRP polyester case
- IP54 protection
- 12 keys keyboard + key for sending messages on Public Address Network
- Both handsfree and handset

HANDSET/HANDS-FREE

WALL MOUNTING

IP54

- 20°C to + 70°C

dimensions mm (W x H x D) 120,0 x 637,0 x 170,0

weight 4,2 kg

P/N 7132841 TT - BCA - 12T



Analog ACB telephone, enclosed into weatherproof metal case

- with door
- protection degree IP65 even if door is open
- 12 keys keyboard
- Handset cord with vandalproof protection

HANDSET

WALL MOUNTING

IP65

- 20°C to + 70°C

dimensions mm (W x H x D) 150,0 x 600,0 x 160,0

P/N 7132841A TT - BCA - 15T



Analog ACB telephone, enclosed into weatherproof metal case

- with door
- protection degree IP65 even if door is open
- 15 keys keyboard
- Handset cord with vandalproof protection

HANDSET

WALL MOUNTING

IP65

- 20°C to + 70°C

dimensions mm (W x H x D) 150,0 x 600,0 x 160,0

Analog Phones with handset

WEATHERPROOF

P/N 7137111 TAS21



Weatherproof analog ACB telephone

- GRP polyester case
- IP66 protection
- both handsfree and handset
- with display
- INOX steel 21-keys keyboard

HANDSET/HANDS-FREE

WALL MOUNTING

IP66

- 25°C to + 60°C

dimensions mm (W x H x D) 227,0 x 293,0 x 135,0

weight 6,28 kg

P/N 7132800 TTH10-32P



Analog ACB flush-mounting telephone

- polyester GRP case
- IP65 protection
- 15 keys keyboard

HANDSET

FLUSH MOUNTING

IP65

- 20°C to + 70°C

dimensions mm (W x H x D) 91,0 x 278,0 x 110,0

weight 700 g

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender

It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines

The unit must be powered @ 230VAC

RAIL DIN MOUNTING

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

Analog Phones handsfree

WEATHERPROOF

P/N 7132670 TAS360 VOX 4M/T



Analog ACB weatherproof and vandalproof handsfree telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- with 24 keys (full 12 keys keyboard + 8 function keys + 4 programmable memory keys) + 1 light

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,8 kg

HANDS-FREE
WALL MOUNTING
IP66
- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7132671 TAS360 VOX 1M/ST



Analog ACB weatherproof and vandalproof handsfree telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- 1 programmable call key + 1 light

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,8 kg

HANDS-FREE
WALL MOUNTING
IP66
- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7132674 TAS360 VOX 4M/ST



Analog ACB weatherproof and vandalproof handsfree telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- 4 programmable call keys + 1 light

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,8 kg

HANDS-FREE
WALL MOUNTING
IP66
- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7132678 TAS360 VOX 8M



Analog ACB weatherproof and vandalproof handsfree telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- 8 programmable call keys + 1 light

dimensions mm (W x H x D) 120,0 x 360,0 x 100,0

weight 3,8 kg

HANDS-FREE
WALL MOUNTING
- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

WEATHERPROOF

P/N 7132675 TAS360 VOX 4M/FM



Analog ACB weatherproof and vandalproof handsfree telephone

- IP66 protection
- die cast "copper free" aluminium alloy case
- flush mounting
- 4 programmable call keys (special for SOS tunnel cabinets)

HANDS-FREE

FLUSH MOUNTING

IP66

- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 120,0 x 360,0 x 90,0

weight 3,8 kg

P/N 7132645 RELAYS CARD



Board with 2 relays

- remote or local control through programmable codes
- equipped also with amplifier for internal or external loudspeaker

Accessory for TAS360VOX telephone series

dimensions mm (W x H) 65,0 x 95,0

P/N 7132712 TASVOX 1M/GRP



Analog telephone for wall mount installation

- Weatherproof IP65 GRP housing
- Hands-free - Full-Duplex conversation
- With 1 direct SOS call key

HANDS-FREE

WALL MOUNTING

- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 2,4 kg

P/N 7132710 TASVOX 1M/GRP-IL



Analog telephone for wall mount installation

- Weatherproof IP65 GRP housing
- Hands-free
- Full-Duplex conversation
- With 1 direct SOS call key

HANDS-FREE

WALL MOUNTING

- 20°C to + 70°C

<Embedded "Inductor Loop" for passengers with hearing difficulties>

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 1,5 kg

WEATHERPROOF

P/N 7132711 TASVOX 1M/GRP-IL I/O



Analog telephone for wall mount installation

- Weatherproof IP65 GRP housing
- Hands-free
- Full-Duplex conversation
- With 1 direct SOS call key

<Embedded "Inductor Loop" for passengers with hearing difficulties, with relay electronic card to perform the remote opening of a door or driving strobes>

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 1,5 kg

HANDS-FREE

WALL MOUNTING

IP65

- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender

It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines

The unit must be powered @ 230VAC

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

RAIL DIN MOUNTING

Analog Phones handsfree aluminium 90x serie

WEATHERPROOF

P/N 7133603 TAS916 VOX



Analog ACB telephone

- flush mounting - weatherproof 4mm thick aluminium alloy plate
- IP65 protection
- 16 keys (full 12 keys keyboard and 4 function keys)

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 975 g

HANDS-FREE

FLUSH MOUNTING

IP65

- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133600 TAS901 VOX



Analog ACB telephone

- flush mounting - weatherproof 4mm thick aluminium alloy plate
- IP65 protection
- 1 programmable call key

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 865 g

HANDS-FREE

FLUSH MOUNTING

IP65

- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133601 TAS904 VOX



Analog ACB telephone

- flush mounting - weatherproof 4mm thick aluminium alloy plate
- IP65 protection
- 4 programmable call keys

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 865 g

HANDS-FREE

FLUSH MOUNTING

IP65

- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N 7133602 TAS908 VOX



Analog ACB telephone

- flush mounting - weatherproof 4mm thick aluminium alloy plate
- IP65 protection
- 8 programmable call keys

dimensions mm (W x H x D) 100,0 x 252,0 x 64,0

weight 865 g

HANDS-FREE

FLUSH MOUNTING

IP65

- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

WEATHERPROOF

P/N 7133644 AMPLIFIER CARD

Accessory for 900 telephone series



Amplifier on board for increasing the output volume of the internal loudspeaker or to connect an external loudspeaker

- It is requiring a local 12 VDC power source

dimensions mm (W x H) 30,0 x 50,0

weight 50 g

P/N 7133676 RELAYS CARD

Accessory for 900 telephone series



Board with 2 relays (to switch door lock, lights, etc.) for remote or local control through programmable codes

dimensions mm (W x H) 27,0 x 65,0

weight 50 g

P/N 7133800 DESK CASE

Accessory for 900 telephone series



Desk case


- natural anodized aluminium; black base
- equipped with screws for mounting telephones of the 900 series

dimensions mm (W x H x D) 105,0 x 265,0 x 160,0

weight 350 g

P/N 7133005 PROTRUDING ROOF

Accessory for 900 telephone series



Protruding aluminium roof

- to be added to the flush mounting telephone plate

dimensions mm (W x H x D) 105,0 x 258,0 x 30,0

Analog Phones handsfree aluminium 90x serie

WEATHERPROOF

P/N 7133006 PROTRUDING CASE

Accessory for 900 telephone series



Anodized aluminium case for protruding wall mounting

- built-in roof for a higher protection from bad weather

dimensions mm (W x H x D) 105,0 x 258,0 x 100,0

P/N 7133004 PROTRUDING CASE

Accessory for 900 telephone series



Natural anodized aluminium case for protruding wall mounting

dimensions mm (W x H x D) 105,0 x 258,0 x 70,0

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender

RAIL DIN MOUNTING



Telephone analog line length extender
It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines
The unit must be powered @ 230VAC

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

Analog Phones handsfree aluminium 95x serie

WEATHERPROOF

P/N 7133502 TASVOX 952/IL



Analog telephone for flush mount installation built on weatherproof IP66 aluminium plate and IP66 rear protection

- Hands-free conversation
- Vandal-proof equipped with 1 direct SOS call key and 1 direct INFO call key
- It is configured with the additional "Inductor Loop" device in order to support the communication with people with a hearing aid

**HANDS-FREE
FLUSH MOUNTING**

**IP66
- 20°C to + 70°C**

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 195,0 x 330,0 x 81,0

weight 1,97 kg

P/N 7133531 TASVOX 951L/SOS



Analog telephone for flush mounting installation built on weatherproof IP65 aluminium plate with protruding aluminium roof

- Hands-free conversation
- Vandal-proof equipped with 1 direct SOS call key

Size and installation details are compatible with Swiss highways and tunnels

**HANDS-FREE
FLUSH MOUNTING**

**IP65
- 20°C to + 70°C**

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 170,0 x 365,0 x 145,0

weight 2,1 kg

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender

It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines

The unit must be powered @ 230VAC

RAIL DIN MOUNTING

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

Analog Phones handsfree aluminium 95x serie

WEATHERPROOF

P/N 7133501 TASVOX 951



Analog telephone for flush mounting installation built on weatherproof IP66 aluminium plate and IP66 rear protection

- Hands-free conversation
- Vandal-proof equipped with 1 direct SOS call key

HANDS-FREE

FLUSH MOUNTING

IP66

- 20°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 195,0 x 330,0 x 81,0

weight 1,97 kg

Analog Phones handsfree steel

WEATHERPROOF

P/N 7133623 TASVOX 1004



- Analog ACB telephone
- flush mounting
 - weatherproof INOX steel plate
 - IP66 protection
 - 4 programmable call keys

HANDS-FREE
FLUSH MOUNTING

- 20°C to + 70°C

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 180,0 x 260,0 x 57,0

weight 1,45 kg

P/N 7133621 TAS1004VOX/ST



- Analog ACB telephone
- flush mounting - weatherproof INOX steel plate
 - IP66 protection
 - no keys, but able to be connected up to 4 programmable external keys
 - Special version for SOS boxes for road tunnels

HANDS-FREE
FLUSH MOUNTING


IP66
- 20°C to + 70°C

Option:
Remote Monitoring by
ASTRO System Manager

dimensions mm (W x H x D) 180,0 x 260,0 x 57,0

weight 1,45 kg

P/N 7133028 Plate



- Aluminium face plate 3mm thickness
- painted yellow RAL1023
 - equipped with 4 mushroom push buttons and screen printed symbols "Ambulance", "Fire", "Police", "Breakdown"
 - for installation of a telephone type TASVOX or TASVOIP 1004 series in a SOS tunnel cabinet

dimensions mm (W x H x D) 496,0 x 748, x 35,0

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender
It allows up to 4 standard analog telephones to operate with a standard PBX up to:

RAIL DIN MOUNTING

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines
The unit must be powered @ 230VAC

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

EXPLOSION-PROOF

P/N 7138150 TAS22AD



Explosion-proof analog ACB telephone

- GRP polyester case
- IP66 protection
- both handsfree and handset
- with display
- INOX steel 21-keys keyboard
- ATEX Certified:

II 2G Ex em[ib] IIC T5/T6

II 2D Ex tb [ib] IIIC T100°C/T80°C Db

HANDSET/HANDS-FREE

WALL MOUNTING

IP66

- 20°C to + 60°C

ATEX

dimensions mm (W x H x D) 227,0 x 293,0 x 135,0

weight 6,36 kg

P/N 7133201 TASVOX AD 1M



Explosion-proof ACB analog telephone

- full-duplex handsfree
- IP66 protection
- both loudspeaker and microphone are explosion-proof
- One key for calling a programmable number.
- ATEX EEx dIIB 2G T4

HANDS-FREE

WALL MOUNTING

IP66

- 20°C to + 70°C

ATEX

dimensions mm (W x H x D) 245,0 x 490,0 x 223,0

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender

It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines

The unit must be powered @ 230VAC

RAIL DIN MOUNTING

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

Analog Phones decontaminable

DECONTAMINABLE

P/N 7133639 SANIVOX 918S



- Analog ACB telephone for clean-rooms
- flush mounting
 - front surface IP66 weatherproof without holes and fully washable by common detergents or bactericides
 - standard keyboard
 - 2 memory keys
 - adjustable receiver volume
 - slim thickness 34mm depth only

HANDS-FREE
FLUSH MOUNTING
IP66
 - 20°C to + 70°C

*Option:
 Remote Monitoring by
 ASTRO System Manager*

dimensions mm (W x H x D) 125,0 x 280,0 x 34,0 weight 800 g

P/N 7133626 SANIVOX 901S



- Analog ACB telephone for clean-rooms
- flush mounting
 - front surface IP66 weatherproof without holes and fully washable by common detergents or bactericides
 - 1 memory key
 - slim thickness 34mm depth only

HANDS-FREE
FLUSH MOUNTING
IP66
 - 20°C to + 70°C

*Option:
 Remote Monitoring by
 ASTRO System Manager*

Product manufactured upon request. MOQ 25 pcs

dimensions mm (W x H x D) 125,0 x 280,0 x 34,0 weight 800 g

P/N 7133627 SANIVOX 904S



- Analog ACB telephone for clean-rooms
- flush mounting
 - front surface IP66 weatherproof without holes and fully washable by common detergents or bactericides
 - 4 memory keys
 - slim thickness 34mm depth only

HANDS-FREE
FLUSH MOUNTING
IP66
 - 20°C to + 70°C

*Option:
 Remote Monitoring by
 ASTRO System Manager*

Product manufactured upon request. MOQ 25 pcs

dimensions mm (W x H x D) 125,0 x 280,0 x 34,0 weight 800 g

P/N 7133628 SANIVOX 908S



- Analog ACB telephone for clean-rooms
- flush mounting
 - front surface IP66 weatherproof without holes and fully washable by common detergents or bactericides
 - 8 memory keys
 - slim thickness 34mm depth only

HANDS-FREE
FLUSH MOUNTING
IP66
 - 20°C to + 70°C

*Option:
 Remote Monitoring by
 ASTRO System Manager*

Product usually available ex-stock

dimensions mm (W x H x D) 125,0 x 280,0 x 34,0 weight 800 g

DECONTAMINABLE

P/N 7133644 **AMPLIFIER CARD**

Accessory for decontaminable SANIVOX telephone sets



Amplifier on board for increasing the output volume of the internal loudspeaker or to connect an external loudspeaker

- It is requiring a local 12 VDC power source

dimensions mm (W x H) 30,0 x 50,0

weight 50 g

P/N 7133676 **RELAYS CARD**

Accessory for decontaminable SANIVOX telephone sets



Board with 2 relays (to switch door lock, lights, etc.) for remote or local control through programmable codes

dimensions mm (W x H) 27,0 x 65,0

weight 50 g

P/N 8131931 **BACK-BOX**

Accessory for decontaminable SANIVOX telephone sets



Galvanized steel back-box for concrete wall installation of SANIVOX-SANIVOIP series telephone sets

- It is not necessary for installation on metal or plastic panels or sandwich panels

dimensions mm (W x H x D) 107,0 x 265,0 x 56,0

weight 400 g

P/N 7133060 **BACK-BOX**

Accessory for decontaminable SANIVOX telephone sets



Stainless steel back-box for surface installation of SANIVOX-SANIVOIP series telephone sets as alternative to the flush mounting installation

dimensions mm (W x H x D) 135,0 x 290,0 x 36,5

weight 440 g

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender
It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines
The unit must be powered @ 230VAC

RAIL DIN MOUNTING

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

Analog Phones without keyboard

INDOOR

P/N 7127525 TONO BC



- Desk/wall mounting analog CB telephone
- antishock resin made case
 - handset is equipped with an ergonomic volume adjustment
 - suitable for emergency communications
 - powered by standard analogue telephone lines, either PTT trunks or PBX internal lines

dimensions mm (W x H x D) 95,0 x 245,0 x 90,0

weight 800 g

HANDSET
DESK/WALL MOUNTING

0°C to + 50°C

WEATHERPROOF

P/N 7132442CF TCS2000 RV



- Analog CB weatherproof and vandalproof telephone
- IP66 protection
 - no keyboard
 - die cast "copper free" aluminium alloy case, (suitable for petro-chemical environments)
 - adjustable volume receiver (Vol + / Vol - keys)
 - adjustable volume loud bell (95 dB at 1m)

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,40 kg

HANDSET
WALL MOUNTING
IP66
- 20°C to + 70°C

P/N J7132806 TTH11



- Weatherproof flush-mounting analog CB telephone
- polyester GRP case
 - IP65 protection

dimensions mm (W x H x D) 91,0 x 278,0 x 110,0

weight 700 g

HANDSET
FLUSH MOUNTING
IP65

P/N J7132805 TTS11 32P



- Weatherproof analog CB telephone
- GRP polyester case
 - wall mounting
 - IP65 protection

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 2,6 kg

HANDSET
WALL MOUNTING
IP65
- 20°C to + 70°C

Analog Phones without keyboard

WEATHERPROOF

P/N 7132840 TT - BC



- Analog CB telephone
- enclosed into weatherproof metal case, with door
 - protection degree IP65 even if door is open
 - handset cord with vandalproof protection

HANDSET
WALL MOUNTING
IP65
- 20°C to + 70°C

dimensions mm (W x H x D) 150,0 x 600,0 x 160,0

EXPLOSION-PROOF

P/N 7138170 TCS22AD



- Explosion-proof analog CB telephone
- GRP polyester case
 - IP66 protection
 - with handset
 - no keyboard
 - ATEX Certified:
II 2G Ex em[ib] IIC T5/T6
II 2D Ex tb [ib] IIIC T100°C/T80°C Db

HANDSET
WALL MOUNTING
IP66
- 20°C to + 60°C
ATEX

dimensions mm (W x H x D) 227,0 x 293,0 x 135,0

weight 6,0 kg

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender
It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines
The unit must be powered @ 230VAC

RAIL DIN MOUNTING

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

HOT-LINE Phones without keyboard

INDOOR

P/N 7127535 TONO "HOT-LINE"



Analog BC telephone desk/wall mounting, without keyboard for emergency communications

- directly powered by standard analog lines
- both by PTT trunks or by PBX extension lines
- Receiving volume adjustment
- red colour

**HANDSET
DESK/WALL MOUNTING**

0°C to + 50°C

dimensions mm (W x H x D) 95,0 x 245,0 x 90,0

weight 800 g

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender

It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines
The unit must be powered @ 230VAC

RAIL DIN MOUNTING

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

EMERGENCY CALL POINTS on board (EN 50155)

P/N 71331xa TASVOICE SERIES 164/1K



SOS / Emergency Call Point for Railway applications

Family of Products expressly manufactured according to Customer specifications.

IP65

- 40°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 106,0 x 164,0 x 53,0

weight 850 g

P/N 71331xc TASVOICE SERIES 164/1K-2LAN



Digital IP intercom for flush mounting installation. Double LAN interfaces for Railway applications.

Family of Products expressly manufactured according to Customer specifications.

IP65

- 40°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 106,0 x 164,0 x 68,0

weight 1,0 kg

P/N 71331xe TASVOICE SERIES 164/2K-2LAN



SOS / Emergency Call Point for Railway applications, double standard Analog/Digital IP intercom for flush mounting installation.

Family of Products expressly manufactured according to Customer specifications.

IP65

- 40°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 120,0 x 180,0 x 70,0

weight 850 g

P/N 71331xd TASVOICE SERIES 164/1K T-TEL



On-board VoIP Emergency Call Point for Metro and Railways applications, with Direct call Button and Call Status visual and audible indications.

IP65

- 40°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

dimensions mm (W x H x D) 106,0 x 164,0 x 53,0

weight 850 g

P/N 71331xg TASVOICE 164-4K ON-BOARD CUSTOM INTERCOM UNIT



CUSTOMIZED COMMUNICATION UNIT FOR METRO DRIVER

dimensions mm (W x H x D)

P/N 71331xf TASVOICE 164 CUSTOMIZED ON-BOARD PHONE UNIT



DRIVER telephone for Metro & Railways

SOS / Emergency Call Point for Railway applications

Family of Products expressly manufactured according to Customer specifications.

IP65

- 40°C to + 70°C

*Option:
Remote Monitoring by
ASTRO System Manager*

P/N D001166 CRUISE SHIP PAGA ACCESS PANEL



Cruise ship PAGA ACCESS PANEL 8 keys

EMERGENCY CALL POINTS for elevators

P/N 7426100 ANALOG INTERCOM ALARM FOR ELEVATOR CAB ROOF



Terminale predisposto per collegamento a PSTN (o interno analogico di PABX)

- diagnosticabile da remoto
- messaggi di conforto antipanico
- chiamata ciclica di prova
- resa acustica in cabina pari a 90 dB a 1 m

P/N 7426142N ELEVATOR INTERCOM UNIT



Unità di cabina a montaggio verticale

Pannello completo di microfono e led per installazione in cabina

P/N 7426140N ELEVATOR INTERCOM UNIT



Unità di cabina a montaggio orizzontale

Pannello completo di microfono e led per installazione in cabina

P/N 7426102 ELEVATOR INTERCOM UNIT FOR MAINTENANCE



Pulsante ALLARME FOSSA +MICROFONO FOSSA con cavo di collegamento lunghezza 6m e connettore

EMERGENCY CALL POINTS for elevators

P/N 7426125 ACCESSORY FOR LIFTVOX - INDUCTOR LOOP



Sistema AFILS (Audio Frequency Induction Loop System)

- alimentatore AC/DC
- amplificatore a corrente costante
- induttore
- cavi di connessione

dimensions 217,0 x 113,0 x 63,0 mm

LINE EXTENDER

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender

It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines

The unit must be powered @ 230VAC

RAIL DIN MOUNTING

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

P/N ASTRO

"ASTRO System Manager"



"ASTRO System Manager" is a client operator station that allows to control a set of remote terminals.

- Emergency Calls
- Diagnostic Data
- Historical Data
- Alarms Events
- Configuration
- Different user access levels each with password protection

dimensions mm (W x H x D) 486,0 x 44,5 x 305,0 mm

*for information please
contact Fitre:
divisione.dsi@fitre.it*

P/N 7549262

ASTRO MANAGER CLIENT UNIT



Astro Manager is a client operator station that allows to control a set of remote terminals.

Astro Manager supervises Public Address Voice Alarms, Emergency and Intercom calls activity.

Analog Local Battery Phones

INDOOR

P/N 7122240 TONO BL/3V



Electronic LB desk/wall telephone

- ABS case
- Line length up to 15km using telephone cable 0.6 mm diameter
- Adjustable receiver volume
- ringer 70 db/1 m
- Power supply 3 to 4.5Vdc • It requires 1 connection box 7122201 or 1 feeding box 7715110 (not included)

HANDSET

DESK MOUNTING

0°C to + 50°C

dimensions mm (W x H x D) 95,0 x 245,0 x 90,0

weight 800 g

P/N 7122201 FEEDING BOX



Feeding box for TONO LB telephone

- it must be equipped with 3 pcs. 1.5V batteries, D type - LR20 (not included)

Accessory for TONO BL/3V telephone set

dimensions mm (W x H x D) 85,0 x 120,0 x 60,0

weight 300 g

P/N 7715110 FEEDING BOX



Feeding box for TONO LB telephone

- with floating 4V sealed battery and charging circuit powered at 230VAC

Accessory for TONO BL/3V telephone set

dimensions mm (W x H x D) 85,0 x 120,0 x 60,0

weight 650 g

WEATHERPROOF

P/N 7131200 TLS2000 3V



Analog LB weatherproof and vandalproof telephone

(it requires 3 pcs. LR20 1,5V batteries - type D - 60 x Ø34 mm usually suitable for at least one years of service)

- IP66 protection
- no keyboard
- die cast "copper free" aluminium alloy case, (suitable for petro-chemical environments)
- equipped with electronic ringer current generator
- adjustable volume loud bell (95 dB at 1m)

HANDSET

WALL MOUNTING

IP66

- 20°C to + 70°C

dimensions mm (W x H x D) 230,0 x 270,0 x 140,0

weight 5,9 kg

Self-Powered Phones

P/N 7111650 CTZ1M TONO



- Self-powered telephone console
- IP50 protection
 - without outgoing calling system (incoming only)

DESK MOUNTING
IP50

dimensions mm (W x H x D) 190,0 x 133,0 x 234,0

weight 2,3 kg

P/N 7111714 CTZ1M-V TONO



- Self-powered telephones console
- IP50 protection
 - with incoming call buzzer and loud ringer interface
 - outgoing calling sound-wheel equipped

DESK MOUNTING
IP50

dimensions mm (W x H x D) 190,0 x 145,0 x 234,0

weight 2,3 kg

P/N 7111627 TM/10AR



- Self-powered wall telephone
- IP65 protection
 - polyester GRP case
 - orange colour
 - outgoing calling sound-wheel equipped

HANDSET
WALL MOUNTING
IP65

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 2,95 kg

P/N 7111xxx TM/10AR



- Self-powered wall telephone
- IP65 protection
 - polyester GRP case
 - orange colour
 - outgoing calling sound-wheel equipped
 - polyester handset cord

HANDSET
WALL MOUNTING
IP65

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 2,95 kg

Self-Powered Phones

P/N 7111626 TL10/GR



- Self-powered wall telephone
- IP65 protection
 - polyester GRP case
 - grey colour
 - outgoing calling sound-wheel equipped

HANDSET
WALL MOUNTING
IP65

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 2,95 kg

P/N 7111628 TM20/GR



- Self-powered wall telephone
- IP65 protection
 - polyester GRP case
 - grey colour
 - outgoing calling sound-wheel equipped
 - with incoming call buzzer

HANDSET
WALL MOUNTING
IP65

dimensions mm (W x H x D) 120,0 x 380,0 x 170,0

weight 2,95 kg

P/N 7111734 TM/C



- Self-powered telephone
- inox wall case
 - with hermetic door
 - IP65 protection
 - outgoing calling sound-wheel equipped

WALL MOUNTING
IP65

dimensions mm (W x H x D) 150,0 x 600,0 x 160,0

P/N 8312201 G701



- Self-powered telephones
- rilsan body
 - without outgoing calling system (incoming only)

Available accessories:

- Holder - P/N 8319203
- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826
- Carrying bag G/320A - P/N 8319812

dimensions mm (W x H x D) 58,0 x 266,0 x 95,0

weight 600 g

Self-Powered Phones

P/N 8312101 G709



Self-powered telephones

- rilsan body
- without outgoing calling system (incoming only) with Push-To-Talk button

Available accessories:

- Holder - P/N 8319203
- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826
- Carrying bag G/320A - P/N 8319812

dimensions mm (W x H x D) 58,0 x 266,0 x 95,0

weight 700 g

P/N 8311321 G711



Weatherproof self-powered telephones

- antistatic elastomer body
- IP66 protection, outgoing calling sound-wheel equipped

Available accessories:

- G30 Holder - P/N 7315630 • G24 Switch Holder - P/N 7315400
- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826
- Carrying bag G/320A - P/N 8319812

dimensions mm (W x H x D) 84,0 x 330,0 x 150,0

weight 1,4 kg

IP65

P/N 8311422 G852



Weatherproof self-powered telephones

- antistatic elastomer body
- IP66 protection
- outgoing calling sound-wheel equipped
- ATEX II 1G Ex ia IIC T6 intrinsical safety certified

Available accessories:

- G30 Holder - P/N 7315630 • G24 Switch Holder - P/N 7315400
- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826
- Carrying bag G/320A - P/N 8319812

dimensions mm (W x H x D) 84,0 x 330,0 x 150,0

weight 1,4 kg

IP66

ATEX

P/N 7148105 S7601



Self-powered headset with headband

- microphone and two earphones
- without outgoing calling generator

Available accessories:

- G24 Switch Holder - P/N 7315400
- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826

weight 650 g

P/N 7148107 S7602/2



Self-powered headset with headband

- microphone and two earphones
- without outgoing calling generator
- certified for explosive atmospheres by Intrinsic Security degree IIC

Available accessories:

- G24 Switch Holder - P/N 7315400
- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826

weight 650 g

P/N 7148109 S7603/2



Self-powered headset with headband

- microphone and two earphones
- with outgoing calling generator to be clipped to the belt
- certified for explosive atmospheres by Intrinsic Security degree IIC

Available accessories:

- G24 Switch Holder - P/N 7315400
- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826

weight 650 g

P/N 7147102 TLP97



- Portable LB amplified weatherproof telephone
- IP66 protection, it requires 2pcs. "stilo" (AA) 1,5V batteries (not included)
 - Distance up to 10 km using telephone copper cable 0,6 mm diameter

IP66

Available accessories:

- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826
- Carrying bag - P/N 8319812

dimensions mm (W x H x D) 73,0 x 246,0 x 77,0

weight 750 g

P/N 7148206 TLP182



- Portable amplified headset
- with belt-box IP50 protection, it requires 2pcs. "stilo"(AA) 1,5V batteries (not included)
 - Distance up to 10 km using telephone copper cable 0,6 mm diameter
 - completely handsfree

IP50

Available accessories:

- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826
- Carrying bag - P/N 8319812

weight 970 g

P/N 8319203 HOLDER



Wall mounting holder

Accessory for:

- G701 - P/N 8312201 • G709 - P/N 8312101 rilsan telephone sets

weight 230 g

P/N 7315630 G30



Wall mounting stainless steel holder

Accessory for:

- G711 - P/N 8311321 • G852 - P/N 8311422 antistatic elastomer telephone sets

dimensions mm (W x H x D) 110,0 x 300,0 x 120,0

weight 1,0 kg

P/N 7315400 G24



Wall mounting holder with hang-up switch

Accessory for:

- G711 - P/N 8311321 • G852 - P/N 8311422 antistatic elastomer telephone sets.
- S7601 - P/N7148105 • S7602/2 - P/N 7148107
- S7603/2 - P/N 7148109 headsets

dimensions mm (W x H x D) 140,0 x 165,0 x 100,0

weight 850 g

P/N 8319812 G320/A



Carrying bag for self-powered & portable telephones equipment

Accessory for:

- G701 - P/N 8312201 • G709 - P/N 8312101 rilsan telephone sets
- G2100 - P/N 8311103 polyamide telephone set
- G711 - P/N 8311321 • G852 - P/N 8311422 antistatic elastomer telephone sets
- TLP97 - P/N 7147102 portable LB amplified telephone
- TLP182 - P/N 7148206 portable LB amplified headset

dimensions mm (W x H x D) 250,0 x 400,0 x 90,0

weight 460 g

Accessories for Self Powered & Portable Phones

P/N 2964156 JACK PLUG



Weatherproof IP54 degree jack plug

Accessory for all Self-Powered and Portable Telephones

IP54

weight 75 g

P/N 8311321 SOCKET



Weatherproof self-powered telephones

- antistatic elastomer body
- IP66 protection, outgoing calling sound-wheel equipped

Available accessories:

- G30 Holder - P/N 7315630 • G24 Switch Holder - P/N 7315400
- Jack Plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826
- Carrying bag G/320A - P/N 8319812

IP54

weight 180 g

P/N 8319825 TS105



Clamp connector for shunting any portable wired telephone and headsets on any point of a TS104 self-healing cable

Accessory for all Self-Powered and Portable Telephones

dimensions mm (W x H x D) 27,0 x 142,0 x 45,0

weight 400 g

P/N 8319826 TS104



2-wires self-healing flat cable, section 2mmq, suitable for the shunting of TS105 clamp connector (packaged in coil of 500 meters)

Accessory for all Self-Powered and Portable Telephones

dimensions mm (W x H) 16,0 x 6,0

weight 120 g/m

INDOOR

P/N 7331250 TRILLO3PN



- Acoustic/luminous ringer for indoor use
- adjustable volume up to 110dB/1m
 - incremental ringtone first ring 99dB / 1m
 - 4 different ring tones
 - different tonality between phone call and bell call
 - input bell call: AC 4 to 24V - DC 4 to 60V - voltage free contact
 - 3 high efficiency LED signaling
 - output for external loudspeaker 8W-4ohm
 - power supply 240V - 50Hz
 - output 12VDC for external relay bridging ringer's breaks for continuous activating of rotating lamps

dimensions mm (W x H x D) 106,0 x 225,0 x 73,0

weight 1,5 kg

**ACOUSTIC / LUMINOUS
WALL MOUNTING**

WEATHERPROOF

P/N 7322255 TRILLO 201 T/E



- Telephone auxiliary ringer
- weatherproof IP55 protection
 - no need of external supply
 - 95dB/1m
 - Adjustable volume and melody

dimensions mm (W x H x D) 106,0 x 140,0 x 73,0

weight 500 g

**ACOUSTIC
WALL MOUNTING
IP55**

P/N 7322260 TRILLO FLASH 201T/E



- Weather proof telephone and bell ringer with XENON flashing lamp
- clear colour
 - Maximum acoustic output 95dB/1m
 - Power supply 48VDC
 - Operation modes: acoustic & optical, acoustic only, optical only

dimensions mm (W x H x D) 106,0 x 140,0 x 120,0

weight 550 g

**ACOUSTIC / LUMINOUS
WALL MOUNTING
IP55**

P/N 7332306 R140 FLASH/220



- Weatherproof luminous/acoustical telephone ringer
- adjustable volume up to 120dB/1m
 - power supply 220 VAC
 - with XENON flashing lamp amber colour
 - IP66 protection

dimensions mm (W x H x D) 192,0 x 240,0 x 170,0

weight 4,5 kg

**ACOUSTIC / LUMINOUS
WALL MOUNTING
IP66
- 35°C to + 70°C**

WEATHERPROOF

P/N 7332310 R140 FLASH/R/220



Weatherproof luminous/acoustical telephone ringer

- adjustable volume up to 120dB/1m
- power supply 220VAC
- with XENON flashing lamp amber colour
- IP66 protection
- equipped with relay for auxiliary rotating beacons driving

**ACOUSTIC / LUMINOUS
WALL MOUNTING**

IP66

- 35°C to + 70°C

dimensions mm (W x H x D) 192,0 x 240,0 x 170,0

weight 4,5 kg

P/N 7322275 TRILLO 201 EN



Weatherproof electrical ringer

- IP55 protection
- 95dB/1m
- Multi-voltage power supply 12 to 24VAC or 48VDC
- Adjustable volume and melody

ACOUSTIC

WALL MOUNTING

IP55

dimensions mm (W x H x D) 106,0 x 140,0 x 73,0

weight 500 g

Telephone Call Repeater Relays

INDOOR

P/N 7331500 R118E



- Multi-voltage telephone electronic ringer's relay
- suitable for loads at 115-230Vac (max 5A) or 24÷48Vdc (max 1A)
 - Indoor version for mounting on DIN rail
 - Two output contacts: one repeats the ringing signal cadence, the other one bridges the call breaks

RAIL DIN MOUNTING

dimensions mm (W x H x D) 91,0 x 72,0 x 71,0

weight 220 g

WEATHERPROOF

P/N 7332230 R118ES



- Multi-voltage telephone electronic ringer's relay
- Features as R118E - P/N 7331500, but mounted into aluminium die cast weatherproof case
 - IP66 protection, (without cable gland)

WALL MOUNTING
IP66

dimensions mm (W x H x D) 165,0 x 140,0 x 66,0

weight 700 g

EXPLOSION-PROOF

P/N 7333140 R118EAD



- Multi-voltage telephone electronic ringer's relay
- Features as R118E - P/N 7331500, but mounted into explosion-proof ATEX case
 - IP66 protection

WALL MOUNTING
IP66

ATEX

dimensions mm (W x H x D) 198,0 x 150,0 x 130,0

weight 3,0 kg

Loudspeakers for Special Application

INDOOR

P/N J7327017 BIVOX



Acoustic diffusion set, equipped with 2 loudspeakers

- impedance 16 ohm (8 ohm + 8 ohm)
- 6 W max output
- for protruding or flush mounting
- vandalproof version

Model specially suitable for city-bus

dimensions mm (W x H x D) 265,0 x 80,0 x 95,0

weight 725 g

WALL MOUNTING

- 20°C to + 60°C

WEATHERPROOF

P/N 7327272 AP44



Weatherproof loudspeaker

- Polypropylene homopolymer
- IP54 protection
- 30W output
- 8 ohm impedance
- Supplied with 2m cable

dimensions mm (W x H x D) 100,0 x 100,0 x 90,0

weight 870 g

WALL MOUNTING

IP54

EXPLOSION-PROOF

P/N 7327418D AP13D/30



Explosion-proof 30W loudspeaker

- IP66 protection
- 8 ohm impedance
- ATEX II 2GD Ex db IIC T6/5

dimensions mm (W x H x D) Ø 500,0 x 580,0

weight 5,600 kg

WALL MOUNTING

IP66

- 20°C to + 40°C

ATEX

P/N 7327419D AP13DT/30



Explosion-proof 30W loudspeaker

- IP66 protection
- with 100V transformer
- ATEX II 2GD Ex db IIC T6/5

dimensions mm (W x H x D) Ø 500,0 x 580,0

weight 5,600 kg

WALL MOUNTING

IP66

- 20°C to + 40°C

ATEX

Loudspeakers Amplified

WEATHERPROOF

P/N J7327016 BIVOX/IR



Acoustic diffusion set

- equipped with 2 amplified loudspeakers
- IP54 protection
- 6 W max output
- for protruding or flush mounting
- vandalproof version
- adjustable volume by remote control (it makes easier putting into service)
- Model specially suitable for city-bus
- Power supply: 24VDC (18VDC to 36VDC)

WALL MOUNTING

IP54

- 20°C to + 60°C

dimensions mm (W x H x D) 265,0 x 80,0 x 95,0

weight 1,140 kg

P/N 7327018 IR100

Accessory for BIVOX/IR loudspeaker



Infrared remote control, suitable for BIVOX/IR diffusion set

P/N 7327156 XP14N/24-48



Amplified 20W loudspeaker

- ABS enclosure
- weatherproof IP55 protection
- supply voltage from 24 to 48VDC

WALL MOUNTING

IP55

dimensions mm (W x H x D) 165,0 x 220,0 x 250,0

weight 1,85 kg

P/N 7327166 XPR14N/24-48



Amplified 15W loudspeaker

- ABS enclosure
- weatherproof IP55 protection
- supply voltage from 24 to 48VDC

WALL MOUNTING

IP55

<Special version including the "self-adjustment" of the output volume, according to the "previous" ambient noise level>

dimensions mm (W x H x D) 165,0 x 220,0 x 250,0

weight 1,85 kg

Loudspeakers Amplified

WEATHERPROOF

P/N 7327375 XP11L/24-48



- Weatherproof horn loudspeaker
- IP65 protection
 - with built-in 25W amplifier
 - Dual supply voltage 24 - 48VDC
 - 2m length provided connecting cable

WALL MOUNTING
IP65

dimensions mm (W x H x D) Ø 315,0 x 345,0

weight 3,45 kg

P/N 7327377 XP11LE/24-48



- Weatherproof horn loudspeaker
- IP65 protection
 - with built-in 25W amplifier
 - Dual supply voltage 24 - 48VDC
 - 80 cm length provided connecting cable and Kit with 6-poles connector

WALL MOUNTING
IP65

dimensions mm (W x H x D) Ø 315,0 x 345,0

weight 3,45 kg

P/N 7327376 XPR11L/24-48



- Waterproof horn loudspeaker • IP65 protection • with built-in 25W amplifier
- Dual supply voltage 24 - 48VDC
 - 2m length provided connecting cable

WALL MOUNTING
IP65

<Special version including the "self-adjustment" of the output volume, according to the "previous" ambient noise level>

dimensions mm (W x H x D) Ø 315,0 x 345,0

weight 3,45 kg

EXPLOSION-PROOF

P/N 7327416D XP13D/24-48



Explosion-proof horn loudspeaker

- IP66 protection
- with built-in 25W amplifier
- Dual supply voltage 24-48VDC
- ATEX IIC T3 certified

WALL MOUNTING

IP66

- 20°C to + 40°C

ATEX

dimensions mm (W x H x D) Ø 500,0 x 580,0

weight 7,0 kg

P/N 7327431D XPR13D/24-48



Explosion-proof horn loudspeaker

- IP65 protection
- with built-in 25W amplifier
- Dual supply voltage 24-48VDC
- ATEX IIC T3 certified

<Special version including the "self-adjustment" of the output volume, according to the "previous" ambient noise level>

WALL MOUNTING

IP66

- 20°C to + 40°C

ATEX

dimensions mm (W x H x D) Ø 500,0 x 580,0

weight 7,0 kg

P/N XP12AD XP12AD/24-48



Explosion-proof horn loudspeaker

- IP66 protection
- with built-in 25W amplifier
- Dual supply voltage 24-48VDC
- ATEX IIC T3 certified

WALL MOUNTING

IP66

- 20°C to + 40°C

ATEX

dimensions mm (W x H x D) Ø 500,0 x 580,0

weight 7,0 kg

P/N 7327363 Kit with 6-poles connector



Armored connecting hose 80 cm length

- weatherproof protection
- threaded inlet (loudspeaker side) 3/8" GAS
- with detached 6-poles plug to be wired to the loudspeaker's cable
- Suitable for 6-poles socket P/N 7327364

weight 480 g

P/N 7327364 Kit with 6-poles socket



6-poles socket, with weatherproof cover and safety hooking

- 2 threaded PG16 entries
- Suitable for 6-poles connector P/N 7327363

WALL MOUNTING

weight 320 g

Surge Protections

P/N 7272735 PR164-1/240



Sur Protector Protection Module for 1 analog or ADSL telephone line

RAIL DIN MOUNTING

dimensions mm (W x H x D) 36,0 x 80,0 x 28,0

weight 125 g

P/N 7272720 PR164-2/240



Sur Protector Multiple Protection Module for 2 analog or ADSL telephone lines

RAIL DIN MOUNTING

dimensions mm (W x H x D) 36,0 x 80,0 x 28,0

weight 125 g

P/N 7272730 PR164-3/240



Sur Protector Multiple Protection Module for 3 analog or ADSL telephone lines

RAIL DIN MOUNTING

dimensions mm (W x H x D) 54,0 x 80,0 x 28,0

weight 187 g

Telephone and Network Line Extenders

INDOOR

P/N 7251174 TRA50/4 Telephone Line Extender



Telephone analog line length extender
It allows up to 4 standard analog telephones to operate with a standard PBX up to:

- 10 km far (by using diam.0.6mm cable pairs), or even
- 15 km far (by using diam.0.9mm cable pairs)

2,5kV galvanic isolation on each one of the 4 lines
The unit must be powered @ 230VAC

RAIL DIN MOUNTING

dimensions mm (W x H x D) 157,0 x 90,0 x 60,0

weight 600 g

P/N 7162020 ReteMatic™ IP-RMH1



The ReteMatic™ Network Infrastructure and its devices have been designed to bring network connection within industrial and harsh environments by combining power line and robust data communication over a single medium, the standard power cable.

RACK MOUNTING

-40°C to +80°C

dimensions 483,0 x 44,0 x 240,0 mm

weight 2,9 kg

ReteMatic™ System components

EXPLOSION-PROOF

P/N 7715644 ReteMatic™ RMF50-EX



The ReteMatic™ Network Infrastructure and its devices have been designed to bring network connection within industrial and harsh environments by combining power line and robust data communication over a single medium, the standard power cable.

IP66

-40°C to +80°C

ATEX ZONE1

dimensions mm (W x H x D) 174,0 x 138,0 x 220,0

weight 4,55 kg

ReteMatic™ System components

P/N 7715641 ReteMatic™ RMF150B-EX



The ReteMatic™ Network Infrastructure and its devices have been designed to bring network connection within industrial and harsh environments by combining power line and robust data communication over a single medium, the standard power cable.

IP66

-40°C to +80°C

ATEX Zone1

dimensions mm (W x H x D) 230,0 x 164,0 x 304,0

weight 8,1 kg

ReteMatic™ System components

P/N 7453101 EMERGENCY PILLARS FOR METRO STATIONS



Family of Products expressly manufactured according to Customer specifications
The pillars is equipped with flush-mounting FITRE manufactured - SOS/INFO telephone sets

dimensions mm (W x H x D) Ø 194,0 x 1.740,0

P/N 7454110 EMERGENCY PILLARS FOR METRO STATIONS



Family of Products expressly manufactured according to Customer specifications
The pillars is equipped with flush-mounting FITRE manufactured - SOS/INFO telephone sets

dimensions mm (W x H x D) Ø 194,0 x 2.000,0

P/N 7454404 EMERGENCY PILLARS FOR HIGHWAYS AND CITY PARKS



Family of Products expressly manufactured according to Customer specifications, for roads and motorways
The pillars is equipped with flush-mounting FITRE manufactured - SOS/INFO telephone sets

GRP 4mm/5,5 mm - IP54 - RAL2009
Basement stainless steel AISI304

dimensions mm (W x H x D) 330,0 x 1.916,0 x 540,0

IP54

P/N D001171 EMERGENCY PILLARS FOR HIGHWAYS AND CITY PARKS



Family of Products expressly manufactured according to Customer specifications, for roads and motorways
The pillars is equipped with flush-mounting FITRE manufactured - SOS/INFO telephone sets

Stainless steel 1 mm, V4A, AISI316, SIA 179 classe II

dimensions mm (W x H x D) 356,0 x 1.934,0 x 317,0

P/N 7454300 SOS PILLAR FOR RAILWAY STATIONS



SOS pillar for Railway Stations - Integrated Emergency Call System with CCTV system for video-surveillance

dimensions mm (W x H x D) 450,0 x 2250,0 x 200,0

P/N D001157 INFO/SOS PILLARS FOR RAILWAYS STATIONS




EMERGENCY PILLAR RAILWAYS STATION
VOIP PHONE INCLUDED
CCTV CAMERA EXCLUDED
STEEL

Family of Products expressly manufactured according to Customer specifications
The pillars is equipped with flush-mounting FITRE manufactured - SOS/INFO telephone sets

IP65

dimensions mm (W x H x D) 500,0 x 2300,0 x 175,0

P/N 5617135 AG/F INOX



Disassemblable acoustic booth stainless steel INOX AISI 304

- satin finished • no paint
- 21dB mean noise reduction
- with support plate suitable for TAS2000, TAS360, IF2000 and TAS22AD FITRE-Phones and Intercoms.

Note: the disassembled acoustic booth allows a substantial reduction of transport and storage costs

INOX AISI 304

*MOST RECOMMENDED
USE IN OIL&GAS
APPLICATIONS*

dimensions mm (W x H x D) 700,0 x 680,0 x 600,0

weight 38,0 kg

P/N 5617147 AG/F YE



Disassemblable acoustic booth stainless steel INOX AISI 304

- painted yellow RAL1021
- 21dB mean noise reduction
- with support plate suitable for TAS2000, TAS360, IF2000, TAS22AD FITRE-Phones and Intercoms.

Note: the disassembled acoustic booth allows a substantial reduction of transport and storage costs

INOX AISI 304

*SUITABLE USE IN
OIL&GAS
APPLICATIONS*

dimensions mm (W x H x D) 700,0 x 680,0 x 600,0

weight 38,0 kg

P/N 5617136 AG/F OR



Disassemblable acoustic booth stainless steel INOX AISI 304

- painted orange RAL2000
- 21dB mean noise reduction
- with support plate suitable for TAS2000, TAS360, IF2000, TAS22AD FITRE-Phones and Intercoms.

Note: the disassembled acoustic booth allows a substantial reduction of transport and storage costs

INOX AISI 304

*SUITABLE USE IN
OIL&GAS
APPLICATIONS*

dimensions mm (W x H x D) 700,0 x 680,0 x 600,0

weight 38,0 kg

P/N 5617166 AGX 92/F



Disassemblable acoustic booth stainless steel INOX AISI 304

- painted yellow color RAL1021
- with support plate suitable for TAS2000, TAS360, IF2000, TAS22AD FITRE-Phones and Intercoms.

Note: the disassembled acoustic booth allows a substantial reduction of transport and storage costs

INOX AISI 304

*SUITABLE USE IN
OIL&GAS
APPLICATIONS*

dimensions mm (W x H x D) 700,0 x 920,0 x 700,0

P/N 5617128 AG/F



Disassemblable acoustic booth galvanized steel

- painted orange RAL2000
- 21dB mean noise reduction
- with support plate suitable for TAS2000, TAS360, IF2000, TAS22AD FITRE-Phones and Intercoms.

Note: the disassembled acoustic booth allows a substantial reduction of transport and storage costs

GALVANIZED STEEL

INDUSTRIAL APPLICATIONS

dimensions mm (W x H x D) 700,0 x 680,0 x 600,0

weight 38,0 kg

P/N 5617140 P52



Plastic protection hood

- yellow colour
- with support plate suitable for TAS2000, TAS360, IF2000, TAS21 FITRE-Phones and Intercoms.

PLASTIC

NOT RECOMMENDED USE IN INDUSTRIAL APPLICATIONS

dimensions mm (W x H x D) 530,0 x 700,0 x 400,0

weight 9,5 kg

P/N 5617161 BPX70-92/F



Booth pillar 1995 mm heigh

- stainless steel INOX AISI 304
- painted yellow color RAL1021.
- Suitable for AG and AGX series of FITRE Acoustic Booths

INOX AISI 304

SUITABLE USE IN OIL&GAS APPLICATIONS

dimensions mm (W x H x D) 450,0 x 1.995,0 x 304,0

weight 35,0 kg

P/N 5617163 BPX70-92



Booth pillar 1995 mm heigh

- galvanized steel
- painted grey color RAL7031
- Suitable for AG and AGX series of FITRE Acoustic Booths

GALVANIZED STEEL

INDUSTRIAL APPLICATIONS

dimensions mm (W x H x D) 450,0 x 1.995,0 x 304,0

weight 40,0 kg

P/N 5617180 Pillar extender

Accessory for BPX70-92 and BPX70-92/F pillars



Pillar extender to 2500 mm height
 • stainless steel INOX AISI 304 • no paint
 • with brackets for installing a luminous/acoustical telephone ringing beacon (R140 or TWIN series)

INOX AISI 304

*MOST RECOMMENDED
 USE IN OIL&GAS
 APPLICATIONS*

P/N 5617141 PILLAR FOR P52 BOOTH



Technoplastic pillar
 • made in gray GRP resin
 • with accessories for fixing P52 protection hood

GRP

*NOT RECOMMENDED
 USE IN INDUSTRIAL
 APPLICATIONS*

dimensions mm (W x H x D) 100,0 x 2.000,0 x 100,0

P/N 8343101 IMS1892PS



Magnetic switch - two position

dimensions mm (W x H x D) 246,0 x 173,0 x 55,0

weight 3,4 kg

P/N 8343201 IMS1892RA



Magnetic switch - automatic reset

dimensions mm (W x H x D) 246,0 x 173,0 x 55,0

weight 3,4 kg

P/N 8343102 IMS1919PS



Magnetic switch - two position

dimensions mm (W x H x D) 97,0 x 270,0 x 54,0

weight 2,0 kg

P/N 8343202 IMS1919RA



Magnetic switch - automatic reset

dimensions mm (W x H x D) 97,0 x 270,0 x 54,0

weight 2,0 kg

P/N 8341101 IMS1927A50/N



Permanent magnet inductor NORTH polarity
 • Max.operating distance 110 mm

dimensions mm (W x H x D) 190,0 x 105,0 x 105,0

weight 3,65 kg

P/N 8341102 IMS1927A50/S



Permanent magnet inductor SOUTH polarity
 • Max.operating distance 110 mm

dimensions mm (W x H x D) 190,0 x 105,0 x 105,0

weight 3,65 kg

P/N 8341103 IMS1927A36/N



Permanent magnet inductor NORTH polarity
 • Max.operating distance 60 mm

dimensions mm (W x H x D) 150,0 x 80,0 x 70,0

weight 1,4 kg

P/N 8341104 IMS1927A36/S



Permanent magnet inductor SOUTH polarity
 • Max.operating distance 60 mm

dimensions mm (W x H x D) 150,0 x 80,0 x 70,0

weight 1,4 kg

P/N 8341201 IMS1895



Permanent magnet inductor
• Max.operating distance 180 mm

dimensions mm (W x H x D) 258,0 x 77,0 x 68,0

weight 3,0 kg

P/N 8341202 IMS1922



Permanent magnet inductor
• Max.operating distance 60 mm

dimensions mm (W x H x D) 200,0 x 60,0 x 60,0

weight 1,3 kg

P/N 7575125 ASTRO EN54-16 PAGA/PAVA SERVER UNIT



ASTRO EN54-16: CERTIFIED FLEXIBILITY

- Power Supply:
wide range 19-36 VDC (nominal 24 VDC)
1.25 A typical, 4 A max
- Network Interfaces:
2 Gigabit Ethernet ports
- Serial Interfaces:
RS-232, RS-485 (opt.RS-422)

-5°C to +60°C

dimensions mm (W x H x D) 435,0 x 300,0 x 44,0

P/N 7571102 ASTRO AF120-24SD ASTRO SYSTEM MANAGER SERVER UNIT



ASTRO VOIP COMMUNICATION SYSTEM:
INDUSTRIAL RELIABILITY MADE FLEXIBLE

- Power Supply:
wide range 19-36 VDC (nominal 24 VDC)
1.25 A typical, 4 A max
- Network Interfaces:
2 Gigabit Ethernet ports
- Serial Interfaces:
RS-232, RS-485 (opt.RS-422)

-5°C to +60°C

dimensions mm (W x H x D) 435,0 x 300,0 x 44,0

P/N 7571181 ASTRO ASMR HA 1U



Astro ASMR High Availability 1U (redundant server unit) equipped with cables to connect to the main server unit. Includes redundancy software to provide “Hot-Spare” redundancy with automatic takeover in case of fault of the main server.

- Powered by PSDV-320AA redundant power supply provided with the main server unit
- Two Solid State Disks, one embedded and one removable, in working + backup configuration with automatic rebuild of the working disk in case of failure
- Two 10/100/1000 Mbps Ethernet ports for redundant network connection

-5°C to +60°C

dimensions mm (W x H x D) 435,0 x 300,0 x 44,0

P/N 7575104 PSDV EN54-16



POWER SUPPLY DISTRIBUTION & VISUALIZATION EN54-16 CERTIFIED

The PSDV module is equipped with:

- 8 opto-isolated voltage contacts inputs to generate alarms;
- 8 opto-isolated voltage free inputs to generate alarms;
- 2 output relays to detect the emission status of the announcement and the system status;
- 2 programmable and supplementary output relays.

RACK MOUNTING

-30°C to +70°C

dimensions mm (W x H x D) 486,0 x 44,5 x 305,0

weight 4,3 kg

P/N 7571111 PSU PSDV-320AA



REDUNDANT POWER SUPPLY PSDV-320AA WITH HANDHELD MICROPHONE AND I/Os

- Redundant 320W Power Supply with: two independent 110-230VAC power inlets and eight 24VDC outputs, fully diagnosed
- Hand-held microphone for emergency paging directly from the cabinet, even in case of server fault
- Eight Inputs (dry contact or 12 to 60VDC) and 4 Relay Outputs (NO/NC)
- Two 10/100/1000 Mbps Ethernet ports for redundant network connection

RACK MOUNTING

-30°C to +60°C

dimensions mm (W x H x D) 486,0 x 44,5 x 305,0

weight 4,3 kg

P/N 7531126 GFX rack



The GFX3200+ series analog VoIP gateways are products designated to provide telephony services with security-enhanced capabilities in the modern complex networks. The GFX3200+ gateway provides a connection platform between traditional POTS lines and the IP network with addition intelligent features like long loop, line testing, polarity reversal, caller ID, call transfer, call waiting etc.

RACK MOUNTING

0°C to +45°C

Rack 19" equipped with two slots for:
 7531127: GFXE0808 (8 FXS + 8 FXO ports)
 7531128: GFXE0016 (16 FXS ports)
 7531129: GFXE1600 (16 FXO ports)

dimensions mm (W x H x D) 445,0 x 45,0,0 x 250,0

weight 3,1 kg

P/N 7531127 GFXE0808



The GFX3200+ series analog VoIP gateways are products designated to provide telephony services with security-enhanced capabilities in the modern complex networks.

The GFX3200+ gateway provides a connection platform between traditional POTS lines and the IP network with addition intelligent features like long loop, line testing, polarity reversal, caller ID, call transfer, call waiting etc.

RACK MOUNTING

0°C to +45°C

Model
 8 FXS ports + 8 FXO ports

dimensions mm (W x H x D) 445,0 x 45,0,0 x 250,0

weight 3,1 kg

P/N 7531128 GFXE0016



The GFX3200+ series analog VoIP gateways are products designated to provide telephony services with security-enhanced capabilities in the modern complex networks.

The GFX3200+ gateway provides a connection platform between traditional POTS lines and the IP network with addition intelligent features like long loop, line testing, polarity reversal, caller ID, call transfer, call waiting etc.

RACK MOUNTING

0°C to +45°C

Model
 16 FXS ports

dimensions mm (W x H x D) 445,0 x 45,0,0 x 250,0

weight 3,1 kg

P/N 7531129 GFXE1600



The GFX3200+ series analog VoIP gateways are products designated to provide telephony services with security-enhanced capabilities in the modern complex networks.

The GFX3200+ gateway provides a connection platform between traditional POTS lines and the IP network with addition intelligent features like long loop, line testing, polarity reversal, caller ID, call transfer, call waiting etc.

Model
16 FXO ports

dimensions mm (W x H x D) 445,0 x 45,0,0 x 250,0

weight 3,1 kg

RACK MOUNTING

P/N 7549349 IP-RACK MOUNTING FRAME



Rack mounting frame 3U to install up to 10 IP-DECT/IP-TRONIC modules into a standard 19" cabinet .

dimensions mm (W x H x D) 483,0 x 216,0 x 132,5

RACK MOUNTING

P/N 7549280 IP-MAG



The IP-MAG card allows interfacing of the non-powered magnetophonic lines and the IP network by managing the call and conversation criteria between the devices in the field and the digital operator station.

- Power supply: 24 VDC (6W)
- Ethernet Connection: RJ45

dimensionsmm (W x H x D) 406, x 128,4 x 100,0 mm

weight 0,7 kg

RACK MOUNTING

- 20°C to + 70°C

P/N 7549283 IP-MAG-EXP



The IP-MAG-EXP board constitutes an expansion of IP-MAG tab and allows you to manage the origin of the calls from multiple dedicated lines by transferring this information to the IP-MAG, and then the unit of ASTRO System Manager control.

In addition, the 8 lines can also serve as a call lines from the center towards the apparatus by means of sending a voltage that will trigger the device ringtone.

The board is powered by the IP-MAG to which it is connected.

dimensionsmm (W x H x D) 30,5 x 128,4 x 100,0 mm

weight 0,7 kg

RACK MOUNTING

- 20°C to + 70°C

P/N 7575106 IP-DAD RACK BASE



Rackmount backplane with 4 slots for IP-DAD modules. The backplane supports a back-up feature, allowing a back-up IP-DAD module to take over in case of failure of one of the operating modules. A double Ethernet interface allows for a redundant network connection for increased safety.

RACK MOUNTING

- 30°C to + 70°C

dimensions mm (W x H x D) 486,0 x 44,0 x 386,0

P/N 7575107 IP-DAD RACK MODULE




Each IP-DAD module control one FPMD power amplifier.

- Standard and Back-up operating modes
- Supports both SIP and Fast PA protocols
- Double Ethernet interface for redundant network connection
- RS485 serial interface for managing the diagnostics of the FPMD power amplifiers
- Analogue audio output towards the power amplifiers, available with a RJ45 connection or through a Balanced output.
- Power supply: 24 VDC nominal (23 to 30 VDC accepted)
- Power consumption: 3.6 W maximum

RACK MOUNTING

- 30°C to + 70°C

P/N 7733131 FPMD RACKMOUNT FRAME



Rackmount frame for standard 19" cabinet for FPMD amplifiers.

- Allows for up to 4 FPMD 125/250 or 2 FPMD 500 or 1 FPMD 500 and 2 FPMD 125/250
- Handles included
- 3U occupancy

RACK MOUNTING

P/N 7733144 FPMD500-AMC



The FPMD class "D" power amplifier series has been designed on the basis of the EN 54-16 standard to guarantee a high level of reliability with an efficient energy footprint.

- EN54-16 certified
- Rated power output @230 Vac: 500 W rms D=2,5%
Power @230 Vac -10%: 470 W rms D=10%
Power @24 Vdc:437 W rms D=10%
- Maximum power consumption 740 W

RACK MOUNTING

-10°C to +45°C

dimensions mm (W x H x D) 200,0 x 130,0 x 395,0

weight 14,8 kg

P/N 7733143 FPMD250-AMC



The FPMD class “D” power amplifier series has been designed on the basis of the EN 54-16 standard to guarantee a high level of reliability with an efficient energy footprint.

- EN54-16 certified
- Rated power output @230 Vac: 250 W rms D=3%
Power @230 Vac -10% : 250 W rms D=10%
Power @24 Vdc 210 W rms D=10%
- Maximum power consumption 410 W

RACK MOUNTING

-10°C to +45°C

dimensions mm (W x H x D) 100,0 x 130,0 x 395,0

weight 9,2 kg

P/N 7733145 FPMD125-AMC



The FPMD class “D” power amplifier series has been designed on the basis of the EN 54-16 standard to guarantee a high level of reliability with an efficient energy footprint.

- EN54-16 certified
- Rated power output @230 Vac: 125 W rms D=0,5%
Power @230 Vac -10%: 125 W rms D=6%
Power @24 Vdc:103 W rms D=10%
- Maximum power consumption 195 W

RACK MOUNTING

-10°C to +45°C

dimensions mm (W x H x D) 100,0 x 130,0 x 395,0

weight 8,4 kg

P/N 7575110 ECxI Rack External Control "x" Interface EN54-16



Rack unit equipped with the following connections:

- a connector for the 24 Vdc input voltage, coming from the PSDV module;
- an Ethernet port (“LAN A”) for the connection to the ASTRO Control Unit;
- an Ethernet port (“LAN B”) for the loop-through connection to the other units;
- 2 opto-isolated inputs (voltage contacts) and 4 output relays.

RACK MOUNTING

-30°C to +70°C

dimensions mm (W x H x D) 486,0 x 44,5 x 305,0

weight 2,9 kg

P/N 7575108 ECBI External Control Beacon Interface EN54-16 - 110/230VAC



The ECBI (External Control Beacon Interface) module manages the switching on of the beacons and oversees to the diagnostics of the power line. Each module is capable of controlling up to 4 connection lines of beacons, through a power contact and the diagnostics of the line, by detecting the conditions of “short circuit”, “open line” and “dispersion to the ground”.

The maximum capacity of each line is 5 A. The power supply of the beacons is typically included from 110 to 230 Vac.

The ECBI module is powered by the ECxI rack unit by means of 24 Vdc voltage, coming from the PSDV module.

RACK MOUNTING

-30°C to +70°C

P/N 7575112 ECBI External Control Beacon Interface EN54-16 - 24/48VDC



The ECBI (External Control Beacon Interface) module manages the switching on of the beacons and oversees to the diagnostics of the power line. Each module is capable of controlling up to 4 connection lines of beacons, through a power contact and the diagnostics of the line, by detecting the conditions of “short circuit”, “open line” and “dispersion to the ground”.

The maximum capacity of each line is 5 A. The power supply of the beacons is typically included from 24 to 48 Vdc. The ECBI module is powered by the ECxI rack unit by means of 24 Vdc voltage, coming from the PSDV module.

RACK MOUNTING

-30°C to +70°C

P/N 7575109 ECRI External Control Relay Interface EN54-16



The ECRI (External Control Relay Interface) module manages output relay contacts (volt free contacts) and opto-isolated inputs. Each ECRI module is able to manage:

- 8 output contacts
- 8 inputs coming from closed contacts or voltages included from 5 to 60 Vdc. The working mode of each input is selected by jumpers based on the ECRI module. The positioning of each jumper determines 2 possible operating modes:
 - “VC”: the input is controlled by a DC voltage;
 - “CC”: the input is controlled by the closing of a free voltage contact.

RACK MOUNTING

-30°C to +70°C

P/N 7327332 AM140



Ambient Noise Microphone for PA and PAGA Systems
ELECTRIC TECHNICAL SPECIFICATIONS

- Supply Voltage Range: 18 to 36 VDC
- Power Consumption: 3W max
- Output: 0 dBm balanced audio
- Ambient Noise Measurement Range: 55 to 95 dBA
- Connection: 4 wires
- Temperature Range: -10°C to +85°C
- Humidity Range: 0% to 98% non-condensing
- Ingress Protection: IP65

IP65

-10°C to +85°C

IP protection degree decoding table

DIN 40050 - IEC 529 (EN 60529)

1st digit: protection against penetration of solid objects

2nd digit: protection against penetration of water

0 no special protection

0 no special protection

1 objects > 50,0 mm

1 vertically dripping water

2 objects > 12,0 mm

2 angled dripping water (15° from the vertical)

3 objects > 2.5 mm

3 sprayed water (60° from the vertical)

4 objects > 1.0 mm

4 splashed and sprayed water (all directions)

5 entry of dust

5 low pressure jet water

6 complete protection against entry of dust

6 sea waves

7 temporary immersion

8 continuous submersion

Classification table for apparatus in explosive areas

ATEX 94/9/CE

	Group I: mines and their surface plants		Group II: surface and other sites		
	cat. M1	cat. M2	cat. 1	cat. 2	cat. 3
explosive atmosphere	present	probably present	always present	probably present	
kind of substance	methane, combustible dust	methane, combustible dust	gases, steams, fogs, dust	gases, steams, fogs, dust	gases, steams, fogs, dust
protection level	very high	high	very high	high	normal
zone correlation			gas zone 0 - dust zone 20	gas zone 1 - dust zone 21	gas zone 2 - dust zone 22

Gas	Dust	
0	20	Permanent or long time or frequent explosive atmospheres
1	21	Occasionally explosive atmospheres
2	22	Rarely explosive atmospheres

example areas with combustible dusts

CE XXX  II 2 D T125°

CE mark notified body potentially explosive atmosphere group category dust (D) - gas (G) certified surface temperature

protection modes:
 e = increased safety
 i = intrinsically safety
 d = flameproof

(max) surface temperature class:
 T1= 450°C - T1= 300°C
 T3= 200°C - T4= 135°C
 T5= 100°C - T6= 85°C

example areas with explosion gases

CE XXX  II 2 G EEx e IIB T4

CE mark notified body potentially explosive atmosphere group category gas (G) - dust (D) explosionproof protection european certification typical gas:
 A = propane
 B = ethylene
 C = hydrogen

more about FITRE

Fitre is a manufacturer with an enviable experience in the industrial telecommunications sector, found in a very complete and wide range of products, offering the most advanced technical solutions for communications in Transports and Heavy Industries as Petrochemical, Power and Industrial Plants and other harsh environments. That is proven by countless worldwide installations.

Strongly focussed to provide real added value and creative problem-solving solutions to its Customers, **Fitre** often is partner with leading manufacturers to supply state-of-the-art products on the whole product range.

With its own Hardware and Software Laboratories, **Fitre** develops systems and equipment based on the most up to date communications technologies, both analogue than VoIP, and corresponding the most stringent certification standards.

It has to be particularly highlighted the Emergency Systems with centralized diagnostic, designed for applications in Oil & Gas Plants, Railway Stations, Tunnels and on-board trains, certified according to EN50155 & EN54-16 rules.

The heart of these systems is "**Astro System Manager**", a perfect integrated digital IP system, modular and flexible for optimally managing the communication services for all these applications.

With the own specific and distinguishing flexibility, each system may be configured meeting all the Customer's specifications, even developing special functions.

Astro is designed for operating as a stand-alone system and

has a modern IP based digital scalable architecture, either in software and in hardware, so that it offers the maximum level of flexibility and modularity and it can be expanded just adding software functions and/or hardware modules.

A common platform for managing both Intercom, Emergency and Public Address functions: thanks to this fully exploitable system setting, **Astro** is the perfect solution to fulfil every communication demands.

Everything is designed for meeting the high sophisticated demand in terms of safety and reliability, proposing redundant as well hierarchic architectures.

If that were not enough, **Fitre** guarantees the maximum level of flexibility and integration of the system respect to the functional point of view, configuring the "**Astro System Call Manager**" according to the Customer's specifications and providing the interfaces with the external systems (also supplied by others) through appropriate standard software tools. The operator has a real-time control of the system status and he can manage even by remote, through a standard Internet connection.

Even in case of long-distance connections between the LAN switch and the intercom/telephone stations, **Fitre** supports own Customers offering **ReteMatic**, the state-of-the-art technology based on two only wires connection, for transporting either the power supply voltage and the digital SIP protocols.

To satisfy all needs, **Fitre** manufactures a very wide range of station types: flush mounting, wall mounting and desk stations, weatherproof and vandal-proof, also with the required customized keys.

highlight



IF-PowerDrill

The most advanced Intercom and PAGA System for exploration Drilling Rigs



ASTRO PAGA

Public Address & General Alarm
EN 54-16
Certification



TASVoIP-952

Digital Emergency/Info
Call Telephone Point



TASVOICE 164/2

SOS Emergency
call point for
on-board Railway
applications



Explosion-proof VoIP Telephone and Intercom Stations

ATEX certified for Zone 1,
either with handset or hands-free,
fully suitable for the Oil & Gas world



Look online at the main
certifications of our Quality
System and our products



AC6528 • T00 • Complete ed.201912.r17 eng A4 qrebv

CommunicationsFirst



COMPANY WITH
ISO 9001
CERTIFIED
QUALITY SYSTEM

www.fitre.it



FITRE S.p.A. • electronics & telecommunications

Head Office and Export Division:
via Valsolda, 15 • 20142 MILANO (Italy)
phone: (+39) 02.8959.01
fax: (+39) 02.8959.0400
info@fitre.it

Offices in ROME and VENICE

Center Export Division:
+39) 02.8959.0318 • fax: (+39) 02.8959.0440 • email: divisione.dsi@fitre.it

